

Page 1 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ATF Additive 250 mL
Art.: 5135

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Additives

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P501-Dispose of contents/container safely.

EUH208-Contains long-chained alkylamine, alkoxylated, Alkyl dithio thiadiazole, Alkyl methacrylate. May produce an allergic reaction.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

Page 2 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.06.2015 / 0007
 Replaces revision of / Version: 01.10.2013 / 0006
 Valid from: 16.06.2015
 PDF print date: 17.06.2015
 ATF Additive 250 mL
 Art.: 5135

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.
 Product can compose a film on the water surface, which can prevent oxygen exchange.

REGULATION (EC) No 648/2004

30 % and more
 aliphatic hydrocarbons

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

methacrylate copolymer	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319

Alkyl alkoxyamine	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	---
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Alkyl methacrylate	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	---
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

A mixture of isomers of C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate	
Registration number (REACH)	01-0000015551-76-XXXX
Index	607-530-00-7
EINECS, ELINCS, NLP	406-040-9
CAS	125643-61-0
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 4, H413

long-chained alkylamine, alkoxylated	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	---
content %	0,1-<2

Page 3 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.06.2015 / 0007
 Replaces revision of / Version: 01.10.2013 / 0006
 Valid from: 16.06.2015
 PDF print date: 17.06.2015
 ATF Additive 250 mL
 Art.: 5135

Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
--	--

Distillates (petroleum), solvent-dewaxed light paraffinic	
Registration number (REACH)	01-2119480132-48-XXXX
Index	649-469-00-9
EINECS, ELINCS, NLP	265-159-2
CAS	64742-56-9
content %	10-40
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	800-172-4 (REACH-IT List-No.)
CAS	398141-87-2
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 2, H411

Alkyl dithio thiadiazole	
Registration number (REACH)	--
Index	---
EINECS, ELINCS, NLP	-
CAS	---
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Sens. 1, H317

Total Xi below classification limit.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Drying of the skin.

Irritation of the skin.

Allergic reaction possible.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

Page 4 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂
Foam
Dry extinguisher
Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Flammable vapour/air mixtures
Oxides of carbon
Oxides of sulphur
Oxides of phosphorus

5.3 Advice for firefighters

Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping
Do not carry cleaning cloths soaked in product in trouser pockets.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Not to be stored in gangways or stair wells.
Store product closed and only in original packing.
Protect against moisture and store closed.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 16.06.2015 / 0007

Replaces revision of / Version: 01.10.2013 / 0006

Valid from: 16.06.2015

PDF print date: 17.06.2015

ATF Additive 250 mL

Art.: 5135

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

(GB) Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

(GB)

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

A mixture of isomers of C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Human - dermal	Short term, systemic effects	DNEL	20	mg/kg	
	Human - dermal	Short term, local effects	DNEL	1	mg/cm2	
	Human - dermal	Long term, systemic effects	DNEL	0,22	mg/kg	
	Human - dermal	Long term, local effects	DNEL	0,006	mg/cm2	
	Environment - freshwater		PNEC	0,0043	mg/l	
	Environment - marine		PNEC	0,00043	mg/l	
	Environment - sediment, freshwater		PNEC	233	mg/kg	
	Environment - sediment, marine		PNEC	23,3	mg/kg	
	Environment - soil		PNEC	189	mg/kg	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection:

Protective nitrile gloves (EN 374)

Permeation time (penetration time) in minutes:

> 480

Minimum layer thickness in mm:

Page 6 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.06.2015 / 0007
 Replaces revision of / Version: 01.10.2013 / 0006
 Valid from: 16.06.2015
 PDF print date: 17.06.2015
 ATF Additive 250 mL
 Art.: 5135

0,4
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection:
 If OES or MEL is exceeded.
 Filter A - P2 EN 14387
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,888 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	166 mm ² /s (40°C)
Viscosity:	26 mm ² /s (100°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

10.4 Conditions to avoid

See also section 7.
Protect from humidity.
Open flame, ignition sources

10.5 Incompatible materials

See also section 7.
Avoid contact with strong oxidizing agents.
Avoid contact with other chemicals.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
See also section 5.2

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

ATF Additive 250 mL

Art.: 5135

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						Based on available data, the classification criteria are not met., Classification based on toxicological analyses.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

methacrylate copolymer

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Serious eye damage/irritation:						Eye Irrit. 2

A mixture of isomers of C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate

Page 8 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	> 2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	> 2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising

long-chained alkylamine, alkoxylated

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1350	mg/kg	Rat		Acute Tox. 4
Acute toxicity, by inhalation:	LD50	220	ppm	Rat		
Skin corrosion/irritation:						Skin Corr. 1B
Respiratory or skin sensitisation:						Skin Sens. 1

Distillates (petroleum), solvent-dewaxed light paraffinic

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	5,53	mg/l/4h	Rat		Mist
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin sensitisation:				Guinea pig		No (skin contact)
Germ cell mutagenicity:				Mammalian	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Mouse		Female, Negative
Reproductive toxicity:				Rat		Negative
Aspiration hazard:						Yes
Symptoms:						drying of the skin., vomiting, nausea

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>10000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Symptoms:						headaches, dizziness, nausea, mental confusion, drowsiness, drowsiness

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Page 9 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

ATF Additive 250 mL
Art.: 5135

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							Mechanical precipitation possible.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment							n.d.a.
Other adverse effects:							n.d.a.

A mixture of isomers of C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>74	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	NOEC/NO EL	21d	>=1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to algae:	EC50	72h	>3	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:							Not readily biodegradable
Bioaccumulative potential:	BCF	35d	260				
Bioaccumulative potential:	Log Pow		9,2				@20°C
Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge		
Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Water solubility:			5	µg/l			@20°C
Water solubility:			0,5	µg/l			

Distillates (petroleum), solvent-dewaxed light paraffinic

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Persistence and degradability:							Inherent
Bioaccumulative potential:	Log Pow		>3				Low

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50		1-10	mg/l			
Toxicity to daphnia:	EC50		1-10	mg/l			
Toxicity to algae:	EC50		10-100	mg/l			
Persistence and degradability:		28d	9,6	%			
Bioaccumulative potential:	BCF		1,4				
Bioaccumulative potential:	Log Pow		4,1				

Page 10 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 16.06.2015 / 0007
 Replaces revision of / Version: 01.10.2013 / 0006
 Valid from: 16.06.2015
 PDF print date: 17.06.2015
 ATF Additive 250 mL
 Art.: 5135

Toxicity to bacteria:	EC50		>1000	mg/l			
-----------------------	------	--	-------	------	--	--	--

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Uncontaminated packaging can be recycled.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Classification code: n.a.

LQ (ADR 2015): n.a.

Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Marine Pollutant: n.a.

Environmental hazards: Not applicable

Transport by air (IATA)

UN proper shipping name:

Transport hazard class(es): n.a.

Packing group: n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Comply with trade association/occupational health regulations.

Regulation (EC) No 1907/2006, Annex XVII

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 11, 12
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Aquatic Chronic — Hazardous to the aquatic environment - chronic
Eye Irrit. — Eye irritation
Skin Corr. — Skin corrosion
Aquatic Acute — Hazardous to the aquatic environment - acute
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
Skin Irrit. — Skin irritation
Skin Sens. — Skin sensitization
Acute Tox. — Acute toxicity - oral
Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV	Biological monitoring guidance value (EH40, UK)
BOD	Biochemical oxygen demand
BSEF	Bromine Science and Environmental Forum
bw	body weight
CAS	Chemical Abstracts Service
CEC	Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration

Page 13 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 16.06.2015 / 0007
Replaces revision of / Version: 01.10.2013 / 0006
Valid from: 16.06.2015
PDF print date: 17.06.2015
ATF Additive 250 mL
Art.: 5135

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.