

Page 1 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 10.12.2012 / 0018
Replaces revision of / Version: 03.11.2011 / 0017
Valid from: 10.12.2012
PDF print date: 11.12.2012
ProLine Diesel Spülung 500ML Art.: 5170

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

ProLine Diesel Spülung 500ML
Art.: 5170

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

System cleaner for vehicle fuel units (diesel engines)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr
Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

Tel.: (+49) 0731-1420-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

R44

Dangerous for the environment, R52-53

Xn, Harmful, R65

R66

2.2 Label elements

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not determined

2.2.2 Labeling according to Directives 67/548/EEC and 1999/45/EC (including amendments)

Symbols: Xn
Indications of danger:

Harmful

R-phrases:

44 Risk of explosion if heated under confinement.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.



Page 2 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

S-phrases:

2 Keep out of the reach of children.
 15 Keep away from heat.
 23 Do not breathe vapour/spray.
 24 Avoid contact with skin.
 56 Dispose of this material and its container to hazardous or special waste collection point.
 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Additions:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119473977-17-XXXX
Index	---
EINECS, ELINCS, NLP	919-164-8 (REACH-IT List-No.)
CAS	(64742-82-1)
content %	80-<100
Classification according to Directive 67/548/EEC	Harmful, Xn, R65 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304 Aquatic Chronic 3, H412
2-Ethylhexylnitrate	
Registration number (REACH)	01-2119539586-27-XXXX
Index	---
EINECS, ELINCS, NLP	248-363-6
CAS	CAS 27247-96-7
content %	5-15
Classification according to Directive 67/548/EEC	Harmful, Xn, R20/21/22 R44 Dangerous for the environment, N, R51 Dangerous for the environment, R53 R66
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), heavy arom.	
Registration number (REACH)	--
Index	649-424-00-3
EINECS, ELINCS, NLP	265-198-5
CAS	CAS 64742-94-5
content %	0,1-<1
Classification according to Directive 67/548/EEC	Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67

Page 3 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336
Solvent naphtha (petroleum), light arom.	
Registration number (REACH)	--
Index	649-356-00-4
EINECS, ELINCS, NLP	265-199-0
CAS	CAS 64742-95-6
content %	0,1-<1
Classification according to Directive 67/548/EEC	Flammable, R10 Irritant, Xi, R37 Dangerous for the environment, N, R51 Dangerous for the environment, R53 Harmful, Xn, R65 R66 R67
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 STOT SE 3, H336

For the text of the R-phrases / H-phrases and classification codes (GHS/CLP), see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.
 Danger of aspiration
 In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation of the eyes
 Product removes fat.
 Dermatitis (skin inflammation)
 Ingestion:
 Oedema of the lungs
 Lung damage
 Chemical pneumonitis (condition similar to pneumonia)
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.
 Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Page 4 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 10.12.2012 / 0018
Replaces revision of / Version: 03.11.2011 / 0017
Valid from: 10.12.2012
PDF print date: 11.12.2012
ProLine Diesel Spülung 500ML Art.: 5170

CO2
Extinguishing powder
Foam
Cool container at risk with water.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon
Oxides of nitrogen
Hydrocarbons
Toxic pyrolysis products.
Danger of explosion
Explosive vapour/air mixture
Dangerous vapours heavier than air.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.
If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Keep away from sources of ignition - Do not smoke.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
Store product closed and only in original packing.
Not to be stored in gangways or stair wells.

GB

Page 5 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Solvent resistant floor
 Do not store with oxidizing agents.
 Store in a well ventilated place.
 Protect from direct sunlight and warming.
 Store cool

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
 500 mg/m³

GB	Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:80- <100
	WEL-TWA: 1000 mg/m ³	WEL-STEL: ---	---
	BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	
GB	Chemical Name	Solvent naphtha (petroleum), heavy arom.	Content %:0,1-<1
	WEL-TWA: 500 mg/m ³ (Aromatics)	WEL-STEL: ---	---
	BMGV: ---	Other information: ---	
GB	Chemical Name	Solvent naphtha (petroleum), light arom.	Content %:0,1-<1
	WEL-TWA: 500 mg/m ³ (Aromatics)	WEL-STEL: ---	---
	BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Solvent resistant protective gloves (EN 374).
 If applicable
 Protective nitrile gloves (EN 374)
 Protective gloves made of polyvinyl alcohol (EN 374)
 Protective Viton gloves (EN 374)
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Page 6 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Respiratory protection:
 If OES or MEL is exceeded.
 Gas mask filter A (EN 14387), code colour brown
 At high concentrations:
 Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown, Clear
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	180 °C
Flash point:	63 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	0,6 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Upper explosive limit:	6,1 Vol-% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%))
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,816 g/ml (15°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm ² /s (40°C)
Explosive properties:	Not determined
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.

Page 7 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

Risk of explosion if heated under confinement.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

ProLine Diesel Spülung 500ML

Art.: 5170

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	t					n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Respiratory tract irritation:						n.d.a.
Repeated dose toxicity:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	~3400	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	13100	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitizing

Page 8 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Germ cell mutagenicity:						Negative
Carcinogenicity:						Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						No (inhalation)
Aspiration hazard:						Yes
Symptoms:						dizziness, unconsciousness, headaches

2-Ethylhexylnitrate						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>9640	mg/kg	Rat		
Acute toxicity, by oral route:						Experiences on persons., Harmful
Acute toxicity, by dermal route:	LDLo	>4800	mg/kg	Rabbit		
Acute toxicity, by dermal route:						Experiences on persons., Harmful
Acute toxicity, by inhalation:	LDLo	>4,6	mg/l/1h	Rat		
Acute toxicity, by inhalation:						Experiences on persons., Harmful
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Reproductive toxicity:	NOAEL	20	mg/kg bw/d			Negative

Solvent naphtha (petroleum), heavy arom.						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						Mild irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Aspiration hazard:						Yes
Symptoms:						dizziness, headaches, drowsiness, dizziness

Solvent naphtha (petroleum), light arom.						
Toxicity/effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>5,2	mg/l/4h	Rat		
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Aspiration hazard:						Yes

SECTION 12: Ecological information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Possibly more information on environmental effects, see Section 2.1 (classification).

ProLine Diesel Spülung 500ML Art.: 5170							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:							n.d.a.
Toxicity to daphnia:							n.d.a.
Toxicity to algae:							n.d.a.
Persistence and degradability:							Isolate as much as possible with an oil separator.
Bioaccumulative potential:							n.d.a.
Mobility in soil:							n.d.a.
Results of PBT and vPvB assessment:							n.d.a.
Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LL50	96h	>10- <100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EL50	48h	100-200	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
Toxicity to daphnia:	NOEC/NOEL	21d	0,28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
Toxicity to algae:	EL50	72h	10-100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Persistence and degradability:		28d	74,7	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
Bioaccumulative potential:	Log Pow		4,2-7,2				
Results of PBT and vPvB assessment:							No PBT substance, No vPvB substance

2-Ethylhexylnitrate							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1,88	mg/l	Brachydanio rerio		
Toxicity to daphnia:	EC50	48h	>12,6	mg/l	Daphnia magna		
Toxicity to algae:	EC50	72h	>12,6	mg/l			
Persistence and degradability:		28d	0	%			Not readily biodegradable
Bioaccumulative potential:	BCF		1332				
Bioaccumulative potential:	Log Pow		3,74-5,24				A notable biological accumulation potential has to be expected (LogPow > 3).
Mobility in soil:	Log Koc		3,8				

Page 10 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Results of PBT and vPvB assessment:						No PBT substance, No vPvB substance
Other information:	AOX		0	%		No

Solvent naphtha (petroleum), heavy arom.

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	1-10	mg/l			
Toxicity to daphnia:	EC50	48h	1-10	mg/l			
Toxicity to algae:	IC50	72h	1-10	mg/l			
Persistence and degradability:							Not readily biodegradable
Bioaccumulative potential:	Log Pow		>3,8-4,8				
Bioaccumulative potential:	BCF		<100				
Other information:	BOD		52	%			

Solvent naphtha (petroleum), light arom.

Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	9,22	mg/l	Oncorhynchus mykiss		
Toxicity to daphnia:	LC50	48h	6,14	mg/l	Daphnia magna		
Toxicity to algae:	EC50	96h	19	mg/l	Selenastrum capricornutum		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixes

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2011):

LQ (ADR 2009):

Environmental hazards:

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name:

n.a.

n.a.

n.a.

n.a.

n.a.

Not applicable

Page 11 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Transport hazard class(es):	n.a.
Packing group:	n.a.
Marine Pollutant:	n.a.
Environmental hazards:	Not applicable

Transport by air (IATA)

UN proper shipping name:	
Transport hazard class(es):	n.a.
Packing group:	n.a.
Environmental hazards:	Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions: Yes

Comply with trade association/occupational health regulations.

Observe youth employment law (German regulation).

Observe law on protection of expectant mothers (German regulation).

Regulation (EC) No 1907/2006, Annex XVII

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections: 2, 3, 8, 9, 11, 12

The following phrases represent the posted R phrases / H phrases, Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

10 Flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

37 Irritating to respiratory system.

44 Risk of explosion if heated under confinement.

51 Toxic to aquatic organisms.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

53 May cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Asp. Tox.-Aspiration hazard

Aquatic Chronic-Hazardous to the aquatic environment - chronic

Acute Tox.-Acute toxicity - oral

Acute Tox.-Acute toxicity - dermal

Acute Tox.-Acute toxicity - inhalation

STOT SE-Specific target organ toxicity - single exposure - narcotic effects

Flam. Liq.-Flammable liquid

STOT SE-Specific target organ toxicity - single exposure - respiratory tract irritation

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

Any abbreviations and acronyms used in this document:

AC Article Categories
 acc., acc. to according, according to
 ACGIH American Conference of Governmental Industrial Hygienists
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOEL Acceptable Operator Exposure Level
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
 BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
 BMGV Biological monitoring guidance value (EH40, UK)
 BOD Biochemical oxygen demand
 BSEF Bromine Science and Environmental Forum
 bw body weight
 CAS Chemical Abstracts Service
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
 CIPAC Collaborative International Pesticides Analytical Council
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 COD Chemical oxygen demand
 CTFA Cosmetic, Toiletry, and Fragrance Association
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 DT50 Dwell Time - 50% reduction of start concentration
 DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEA European Economic Area
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ERC Environmental Release Categories
 ES Exposure scenario
 etc. et cetera
 EU European Union
 EWC European Waste Catalogue
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 HET-CAM Hen's Egg Test - Chorionallantoic Membrane
 HGWP Halocarbon Global Warming Potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC Intermediate Bulk Container
 IBC (Code) International Bulk Chemical (Code)
 IC Inhibitory concentration
 IMDG-code International Maritime Code for Dangerous Goods

Page 13 of 14
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revised on / Version: 10.12.2012 / 0018
 Replaces revision of / Version: 03.11.2011 / 0017
 Valid from: 10.12.2012
 PDF print date: 11.12.2012
 ProLine Diesel Spülung 500ML Art.: 5170

incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 LC lethal concentration
 LC50 lethal concentration 50 percent kill
 LCLo lowest published lethal concentration
 LD Lethal Dose of a chemical
 LD50 Lethal Dose, 50% kill
 LDLo Lethal Dose Low
 LOAEL Lowest Observed Adverse Effect Level
 LOEC Lowest Observed Effect Concentration
 LOEL Lowest Observed Effect Level
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 NIOSH National Institute of Occupational Safety and Health (United States of America)
 NOAEC No Observed Adverse Effective Concentration
 NOAEL No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL No Observed Effect Level
 ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

Page 14 of 14
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revised on / Version: 10.12.2012 / 0018
Replaces revision of / Version: 03.11.2011 / 0017
Valid from: 10.12.2012
PDF print date: 11.12.2012
ProLine Diesel Spülung 500ML Art.: 5170

is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.