

Parts list and mounting instructions

Order No.: 7391 D HO VT 125 Shadow

Article: Protection Guard

1 Protection guard

1 x Parts list and mounting instructions

Mounting parts on top:

2 x Hexagon Screw

DIN 933

M 6 x 30 mm

2 x Lock washer

DIN 6797

M 6

2 x Washer

DIN 125

M 6

Mounting parts below right:

2 x Hexagon Screw

DIN 933

M 8 x 20 mm

2 x Washer

DIN 125

M 8

2 x Distance washer

18 x 4 x 5 mm

1 x Ribbed inserts for tube ends

SRL 25

Mounting parts below left:

1 x Distance tube

20 x 4 x 53 mm

1 x Ribbed inserts for tube ends

SRL 25



Picture 7391

Datum/Name	Erstellt	Geändert	Geprüft Entwicklung	Geprüft Verkauf	Freigabe

Mounting instructions:

- For mounting you must change the position of the horn.
- On the left side change the original distance tube against our distance tube., to do that must be dismantled the forward controls
- On the right side the original distance tube goes 5 mm outside. The 5 mm distance tubes you need as distance between engine holder and frame.



Mounting on top (Picture 7391_MO)



Mounting left (Picture 7391_ML)



Mounting right (Picture 7391_MR1)



Mounting right (Picture 7391_MR2)

Care and servicing:

To reach a long live span of our chromium-plated articles they should be cleaned regularly and be treated with customary chrome care means.

With powder coated articles a regular cleaning is important. Damages (e.g. by rockfall) can be mended with colour.

By both versions we recommend about the winter the spraying or rubbing with corrosion protection oil or silicone.

All fixing bolts must be checked at regular intervals (max. 6 months).

We wish you a lot of joy and accident-free journey with our motorcycle accessories.