

## Parts list and mounting instruction

**Order No.:** 7424 MS SU GSF 1250 Bandit

**Article:** Engine Guard, black

**1 pair of guards**

1 x Parts list and mounting instruction

**Mounting parts on top right:**

1 x Strap straight

Strap on frame:

|                              |         |                |
|------------------------------|---------|----------------|
| 1 x threaded rod             | DIN 975 | M 10 x 270 mm  |
| 2 x washer                   | DIN 125 | M 10           |
| 2 x Self locking hexagon nut | DIN 985 | M 10           |
| 1 x distance tube            |         | 18 x 4 x 25 mm |

Engine Guard on strap:

|                   |         |              |
|-------------------|---------|--------------|
| 1 x Hexagon Screw | DIN 933 | M 10 x 25 mm |
| 1 x washer        | DIN 125 | M 10         |

**Mounting parts on top left:**

1 x Strap triple angled

Strap on frame:

|                   |         |                |
|-------------------|---------|----------------|
| 1 x Hexagon Screw | DIN 933 | M 8 x 30 mm    |
| 1 x washer        | DIN 125 | M 8            |
| 1 x distance tube |         | 18 x 4 x 10 mm |

Engine Guard on strap:

|                   |         |              |
|-------------------|---------|--------------|
| 1 x Hexagon Screw | DIN 933 | M 10 x 25 mm |
| 1 x washer        | DIN 125 | M 10         |

**Mounting parts middle right and left:**

|                              |         |             |
|------------------------------|---------|-------------|
| 2 x Counterstrap stamped     |         |             |
| 4 x hexagon socket screw     | DIN 912 | M 6 x 35 mm |
| 4 x Self locking hexagon nut | DIN 985 | M 6         |

**Mounting parts below right and left:**

|                   |         |                     |
|-------------------|---------|---------------------|
| 2 x Hexagon Screw | DIN 960 | M 10 x 1.25 x 60 mm |
| 2 x washer        | DIN 125 | M 10                |
| 2 x distance tube |         | 18 x 4 x 10 mm      |



Picture 7424

| Datum/Name | Erstellt      | Geändert | Geprüft Entwicklung | Geprüft Verkauf | Freigabe |
|------------|---------------|----------|---------------------|-----------------|----------|
|            | 2010-09-03 PK |          |                     |                 |          |

## Mounting instruction:

- Change by the upper fastening the original threaded rods for ours.
- Push the distance tube 18 x 4 x 25 on the right side on the threaded rod.
- Mount in the upper fastening the straps with the listed mounting parts.
- Mount the Protection Guard with the further listed mounting parts loose in the motorcycle, Protection Guard aim and screw together.
- The distance tubes are mounted in each case between Protection Guard and Frame.



Picture 7424\_M

### Care and servicing:

To reach a long live span of our chromium-plated articles they should be cleaned regularly and be treated with customary chrome care means.

With powder coated articles a regular cleaning is important. Damages (e.g. by rockfall) can be mended with colour.

By both versions we recommend about the winter the spraying or rubbing with corrosion protection oil or silicone.

All fixing bolts must be checked at regular intervals (max. 6 months).

**We wish you a lot of joy and accident-free journey with our motorcycle accessories.**