

Parts list and mounting instructions

Order No.: 7490 MS YA FZS 600 Fazer

Article: Engine guard (3point mounting), black

1 pair of guards

1 x Parts list and mounting instructions

Mounting parts on top right and on the left:

2 x Strap 25 x 5 x 120 mm

2 x Hexagon screw

DIN 933

M 10 x 25 mm

2 x Lock washer

DIN 6797

M 10

2 x Washer

DIN 125

M 10

2 x Hexagon screw

DIN 931

M 10 x 100 mm

4 x Washer

DIN 125

M 10

2 x Self locking hexagon nut

DIN 985

M 10

2 x hexagonal cap

SW 17

Mounting parts middle on the right:

1 x Strap 25 x 5 x 58 mm

1 x Hexagon screw

DIN 933

M 10 x 25 mm

1 x Lock washer

DIN in 6797

M 10

1 x Washer

DIN 125

M 10

1 x Hexagon screw

DIN 931

M 8 x 120 mm

2 x Washer

DIN 125

M 8

1 x Self locking hexagon nut

DIN 985

M 8

1 x Distance tube

18 x 4 x 10 mm

1 x hexagonal cap

SW 13

Mounting parts middle on the left:

1 x Strap 25 x 5 x 58 mm

1 x Hexagon screw

DIN 933

M 10 x 25 mm

1 x Lock washer

DIN in 6797

M 10

1 x Washer

DIN 125

M 10

1 x Hexagon screw

DIN 931

M 8 x 130 mm

2 x Washer

DIN 125

M 8

1 x Self locking hexagon nut

DIN 985

M 8

1 x Distance tube

18 x 4 x 20 mm

1 x hexagonal cap

SW 13

Mounting parts below right:

1 x Tubeclamp **without rubber inlet**

DIN 3016 E1

25 x 25 W 1

1 x Hexagon screw

DIN 933

M 10 x 25 mm

2 x Washer

DIN 125

M 10

1 x Self locking hexagon nut

DIN 985

M 10

Mounting parts below left:

1 x Tubeclamp clamp

DIN 3016 E1

30 x 25 W 1

1 x Hexagon screw

DIN 933

M 10 x 25 mm

2 x Washer

DIN 125

M 10

1 x Self locking hexagon nut

DIN 985

M 10

Datum/Name	Erstellt	Geändert	Geprüft Entwicklung	Geprüft Verkauf	Freigabe
	2010-08-12				



Picture 7490

Mounting instructions:

- Mount the Straps with M 10 x 25 screws, Lock washers and Washers in the Protection guard.
- Mount the Protection guard with the further listed mounting parts in the motorcycle.
- The Distance tubes by the mounting point middle are mounted between the Strap and the frame.

Care and servicing:

To reach a long live span of our chromium-plated articles they should be cleaned regularly and be treated with customary chrome care means.

With powder coated articles a regular cleaning is important. Damages (e.g. by rockfall) can be mended with colour.

By both versions we recommend about the winter the spraying or rubbing with corrosion protection oil or silicone.

All fixing bolts must be checked at regular intervals (max. 6 months).

We wish you a lot of joy and accident-free journey with our motorcycle accessories.