according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC MoS2 rust remover 750 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Rust remover

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Johannes J. Matthies GmbH & Co. KG

Street: Hammerbrookstr. 97 Place: D-20097 Hamburg Telephone: + 49 (0) 40 2 37 21-0 e-mail: info@matthies.de Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

Place: GB-NN17 5DP Corby Telephone: + 44 1536 265633 e-mail: info@larsson.uk.com Internet: www.larsson.uk.com + 44 1536 265633

1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

Keep out of reach of children. P102

P101 If medical advice is needed, have product container or label at hand.

according to Regulation (EC) No 1907/2006

	JMC MoS2 rust remover 750 ml	
Revision date: 28.08.2019	Product code: 5540028	Page 2 of 11

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification	•	•			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	918-481-9		01-2119457273-39			
	Asp. Tox. 1; H304 EUH066					
75-28-5	isobutane			25 - < 50 %		
	200-857-2	601-004-00-0	01-2119485395-27			
	Flam. Gas 1, Liquefied gas; H220 H280					
74-98-6	propane		3 - < 5 %			
	200-827-9	601-003-00-5	01-2119486944-21			
	Flam. Gas 1, Liquefied gas; H220 H280					
106-97-8	butane					
	203-448-7	601-004-00-0	01-2119474691-32			
	Flam. Gas 1, Liquefied gas; H220 H280					

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 3 of 11

rinsing.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness, fatique, Skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist. Foam0 Carbon dioxide (CO2)0 Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Gases of varying toxicity can be created through incomplete combustion and thermolysis. In the case of hydrocarbonic products (e.g. CO, CO2, aldehydes and soot). These can be extremely hazardous if inhaled in high concentrations or enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Personal protection equipment: see section 8

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 4 of 11

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe statutory rules and regulations.

Hints on joint storage

Do not store together with: Oxidizing agent0 Pyrophoric or self-heating substances0 Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe statutory rules and regulations.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or shift

c in long-term exposure: after several shifts

d prior to next shift

- Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept
- Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

U: Urea

B: blood

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eve/face protection

Suitable eye protection: Wear safety glasses.

DIN EN 166

Hand protection

Apply skin protection cream for preventive skin protection.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber).

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 5 of 11

Breakthrough time (maximum wearing time): 480min

Thickness of the glove material: 0,45 mm

DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus: gas filtering equipment (EN 141).

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe statutory rules and regulations.

Environmental exposure controls

Observe statutory rules and regulations.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

- 11,7 °C

Flash point:

-80 °C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 1 vol. %
Upper explosion limits: 11 vol. %

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density (at 20 °C): 0,792 g/cm³ DIN 51757

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient: not determined
Viscosity / kinematic: 1,3 mm²/s
Vapour density: not determined

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 6 of 11

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

Details relate to active technical agent.: Relative density, Colour, Odour, Viscosity, pH

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances

10.6. Hazardous decomposition products

Gases of varying toxicity can be created through incomplete combustion and thermolysis. In the case of hydrocarbonic products (e.g. CO, CO2, aldehydes and soot). These can be extremely hazardous if inhaled in high concentrations or enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No								
	Exposure route	Dose		Species	Source	Method		
64742-48-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			yclics, < 2% aromatics					
	oral	LD50 mg/kg	> 8000	Rat	Manufacturer			
	dermal	LD50 > 3160 F mg/kg		Rabbit	Manufacturer			
	inhalation (4 h) vapour	LC50	4951 mg/l	Rat	Manufacturer			
75-28-5	isobutane							
	inhalation vapour	LC50	1237 mg/l	Mouse				
106-97-8 butane								
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 7 of 11

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 8 of 11

CAS No	No Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics								
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Scenedesmus subspicatus				
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna (Big water flea)				
75-28-5	isobutane								
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Piscis	US EPA			
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT			
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT			
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	US EPA			
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT			
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT			
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	US EPA			
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT			
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia Spec.	US EPA OPPT			

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 9 of 11

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml Revision date: 28.08.2019 Product code: 5540028 Page 10 of 11

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC). **National regulatory information**

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

according to Regulation (EC) No 1907/2006

JMC MoS2 rust remover 750 ml

Revision date: 28.08.2019 Product code: 5540028 Page 11 of 11

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

VwVwS: Verwaltungsvorschrift wassergefährdende Stoffe (17. Mai 1999)

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

	0 0 1
Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)