

Trade name: ERC System Reiniger Benzinmotoren**Product no.:** 1100**Current version :** 3.0.4, issued: 03.11.2021**Replaced version:** 3.0.3, issued: 14.09.2020**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****ERC System Reiniger Benzinmotoren****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Additive for mineral oil products

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet**Address**ERC Additiv GmbH
Bäckerstraße 11-13
21244 Buchholz
Germany

Telephone no. +49 4181 216-500

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aquatic Chronic 3; H412

Asp. Tox. 1; H304

Skin Sens. 1; H317

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)

(tetrapropenyl)succinic acid

Hazard statement(s)

H304

May be fatal if swallowed and enters airways.

Trade name: ERC System Reiniger Benzinmotoren**Product no.:** 1100**Current version :** 3.0.4, issued: 03.11.2021**Replaced version:** 3.0.3, issued: 14.09.2020**Region:** GB

H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement(s)

P280 Wear protective gloves/eye protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P331 Do NOT induce vomiting.

2.3 Other hazards

PBT assessment
 No data available.

vPvB assessment
 No data available.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration
			%
1	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)		
-	925-653-7	EUH066 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 25.00 - < 50.00 wt%
-	01-2119458869-15		
2	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)		
-	920-360-0	Asp. Tox. 1; H304 EUH066	>= 25.00 - < 50.00 wt%
-	01-2119448343-41		
3	SOLVENT NAPHTHA (PETROLEUM), HEAVY AROMATIC		
-	64742-94-5	Aquatic Chronic 2; H411	>= 5.00 - < 10.00 wt%
-	265-198-5	Asp. Tox. 1; H304	
-	649-424-00-3	EUH066	
-		STOT SE 3; H336	
4	Polyether polyol		
-		Aquatic Chronic 3; H412	>= 5.00 - < 10.00 wt%
-			
-			
5	Polyolefin alkyl phenol alkyl amine		
-		Skin Irrit. 2; H315	>= 5.00 - < 10.00 wt%
-			
-			
6	1,2,4-trimethylbenzene		
-	95-63-6	Acute Tox. 4*; H332	< 2.50 wt%
-	202-436-9	Aquatic Chronic 2; H411	
-	601-043-00-3	Eye Irrit. 2; H319	
-		Flam. Liq. 3; H226	
-		Skin Irrit. 2; H315	
-		STOT SE 3; H335	
7	naphthalene		

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

	91-20-3 202-049-5 601-052-00-2 -	Acute Tox. 4*; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Carc. 2; H351	< 1.00	wt%
8	(tetrapropenyl)succinic acid			
	27859-58-1 248-698-8 - -	Aquatic Chronic 4; H413 Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1A; H317	< 0.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16
(* , ** , *** , ****) Detailed explanation pls. refer to CLP regulation No. 1272/2008, annex VI, 1.2

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
7	533 mg/kg bodyweight		

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of persisting adverse effects, consult a physician.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

In case of contact with skin wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting - aspiration hazard. Rinse the mouth thoroughly with water. Never give anything by mouth to an unconscious person. If individual is drowsy or unconscious, place in recovery position (on left side, with head down).

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray jet; Foam; Carbon dioxide; Extinguishing powder

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon dioxide (CO₂); Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear protective clothing. Cool endangered containers with water spray jet. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place.

Recommended storage temperature

Value < 50 °C

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep only in the original container. Protect from heat and direct sunlight.

Incompatible products

Do not store together with: Acids; Alkalies; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	1,2,4-trimethylbenzene	95-63-6	202-436-9
	2000/39/EC		
	1,2,4-Trimethylbenzene		
	WEL long-term (8-hr TWA reference period)	100	mg/m ³ 20 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Trimethylbenzenes, all isomers or mixtures		

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

	WEL long-term (8-hr TWA reference period)	125	mg/m ³	25	ppm
2	naphthalene	91-20-3		202-049-5	
	91/322/EWG				
	Naphtalene				
	WEL long-term (8-hr TWA reference period)	50	mg/m ³	10	ppm

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol, vapour and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. combination filter

Respirator EN14387-A

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material In case of short-term contact / splash protection: PVC

Material thickness 0.8 mm

Breakthrough time 4 h

Other

Normal chemical work clothing.

Appropriate Material cotton

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
liquid	
Various, depending on coloration	
Odour	
No data available	
pH value	
No data available	
Boiling point / boiling range	
Value	> 160 °C
Melting point/freezing point	
No data available	
Decomposition temperature	
No data available	
Flash point	
Value	> 61 °C

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

Ignition temperature	
No data available	
Flammability	
No data available	
Lower explosion limit	
No data available	
Upper explosion limit	
No data available	
Vapour pressure	
No data available	
Relative vapour density	
No data available	
Relative density	
No data available	
Density	
No data available	
Solubility	
No data available	
Partition coefficient n-octanol/water (log value)	
No data available	
Viscosity	
Value	< 20.5 mm ² /s
Reference temperature	40 °C
Type	kinematic
Particle characteristics	
No data available	

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Dangerous reactions are not expected if the product is handled according to its intended use.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

Dangerous reactions are not to be expected when handling product according to its intended use.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity		
No	Substance name	CAS no. EC no.

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	4150	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA		
2	naphthalene	91-20-3	202-049-5
LD50	>	533	mg/kg bodyweight
Species	rat		
Source	ECHA		

Acute dermal toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Method	OECD 402		
Source	ECHA / Read across		

Acute inhalational toxicity (result of the ATE calculation for the mixture)

No	Product Name
1	ERC System Reiniger Benzinmotoren
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
LC50	>	5.28	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Skin corrosion/irritation

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Species	rabbit		
Method	OECD 405		
Source	ECHA / Read across		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Respiratory or skin sensitisation

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA / Read across	
Evaluation		non-sensitizing	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Germ cell mutagenicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	-	920-360-0
Source		ECHA / Read across	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard

No data available

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity****Toxicity to fish (acute)**

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

No data available

Toxicity to algae (acute)
No data available

Toxicity to algae (chronic)
No data available

Bacteria toxicity
No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
--	------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is not subject to Part 1 or 2 of Annex I.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information**Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Trade name: ERC System Reiniger Benzinmotoren

Product no.: 1100

Current version : 3.0.4, issued: 03.11.2021

Replaced version: 3.0.3, issued: 14.09.2020

Region: GB

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 734382