

Johannes J. Matthies GmbH & Co. KG

Telefax: + 49 (0) 40 2 37 21-363

Safety Data Sheet

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC Cockpit spray

UFI: Q51X-SX2H-AG0R-4WPV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Johannes J. Matthies GmbH & Co. KG

 Street:
 Hammerbrookstr. 97

 Place:
 D-20097 Hamburg

 Telephone:
 + 49 (0) 40 2 37 21-0

E-mail: info@matthies.de Internet: www.matthies.de

Responsible Department: Abteilung Produktsicherheit

Supplier

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

 Place:
 GB-NN17 5DP Corby

 Telephone:
 + 44 1536 265633

 E-mail:
 info@larsson.uk.com

 Internet:
 www.larsson.uk.com

 1.4. Emergency telephone
 + 44 1536 265633

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane

Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 2 of 15

Pictograms:







Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH208 Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 3 of 15

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied	gas; H220 H280		
	Hydrocarbons, C7-C9,	n-alkanes, isoalkanes, cyclics, < 5% h	exane	25 - < 30 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2 H411	2, STOT SE 3, Asp. Tox. 1, Aquatic Cl	nronic 2; H225 H315 H336 H304	
64742-49-0	Hydrocabons, C7, n-alk	25 - < 50 %		
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2 H411	2, STOT SE 3, Asp. Tox. 1, Aquatic Cl	nronic 2; H225 H315 H336 H304	
74-98-6	propane	10 - < 20 %		
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied	gas; H220 H280		
106-97-8	butane	0,1 - < 1 %		
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied	gas; H220 H280		
5989-27-5	(R)-p-mentha-1,8-diene	0,1 - < 1 %		
	227-813-5	601-096-00-2		
	Flam. Liq. 3, Skin Irrit. 2 H315 H317 H304 H400			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Specific Con	C. LIIIIIIS, WI-IAC	tors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
	921-024-6	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	25 - < 30 %
	inhalation: LC5 5000 mg/kg	0 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >	
64742-49-0	927-510-4	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics	25 - < 50 %
	inhalation: LC5 5500 mg/kg	0 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 =	
106-97-8	203-448-7	butane	0,1 - < 1 %
	inhalation: LC5	0 = 658 ppm (gases)	
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene; d-limonene	0,1 - < 1 %
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg Aquatic Acute 1; H400: M=1	

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes (Limonene, Citral).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 4 of 15

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After indestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, Nausea, Dizziness,

Causes mild skin irritation. May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 5 of 15

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe in addition any national regulations!

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe in addition any national regulations!

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5%	hexane		
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	608 mg/m³
Consumer DN	Consumer DNEL, long-term		systemic	699 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	149 mg/kg bw/day

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

- Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept
- Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Whole blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Tightly sealed safety glasses. (DIN EN 166)

Hand protection

Protect skin by using skin protective cream.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber).

Breakthrough time: 480min

Thickness of the glove material: 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Respiratory protection necessary at: (exceeding exposure limit values) Suitable respiratory protection apparatus: gas filtering equipment (EN 141).

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer. Observe in addition any national regulations!

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 7 of 15

Environmental exposure controls

Observe in addition any national regulations!

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic
Odour threshold: not determined

Test method

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

-40 °C

boiling range:

Flash point: -80 °C

Flammability

Solid/liquid:

Lower explosion limits:

1,1 vol. %

Upper explosion limits:

10,8 vol. %

Auto-ignition temperature:

No information available.

Decomposition temperature:

not determined

Vapour pressure:

not determined

Density (at 20 °C): 0,705 g/cm³ DIN 51757

No information available.

Water solubility: practically insoluble

Solubility in other solvents

not determined

Vapour pressure:

Partition coefficient n-octanol/water:

Viscosity / kinematic:

Relative vapour density:

not determined

not determined

9.2. Other information

Data apply to the technically active substance. Relative density, Colour, Odour, Viscosity, pH

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 8 of 15

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	Hydrocarbons, C7-C9, n-	-alkanes, isoa	lkanes, cyc	lics, < 5% hexane				
	oral	LD50 mg/kg	> 5000	Rat	Manufacturer			
	dermal	LD50 3100 mg/kg	> 2800 -	Rat	Manufacturer			
	inhalation (4 h) vapour	LC50 mg/l	> 25,2	Rat	Manufacturer			
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics							
	oral	LD50 mg/kg	5500	Rat	Manufacturer			
	dermal	LD50 3100 mg/kg	> 2800 -	Rat	Manufacturer			
	inhalation (4 h) vapour	LC50 mg/l	> 23,3	Rat	Manufacturer	OECD 403		
106-97-8	butane							
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS			
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene							
	oral	LD50 mg/kg	> 5000	Rat	GESTIS			
	dermal	LD50 mg/kg	> 5000	Rabbit	GESTIS			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 9 of 15

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane; Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 10 of 15

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
75-28-5	isobutane								
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
	Hydrocarbons, C7-C9, n-a	alkanes, isc	alkanes, cyc	lics, < 5%	hexane				
	Acute fish toxicity	LC50 mg/l	> 1 - 10	96 h	Pimephales promelas (fathead minnow)	Manufacturer			
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Manufacturer	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna	Manufacturer			
64742-49-0	Hydrocabons, C7, n-alkar	nes, iso-alka	anes, cyclics						
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer (Study report(1995))	OECD 201		
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	Manufacturer	SIDS IARF SIAM		
	Acute crustacea toxicity	EC50 mg/l	> 1 - 10	48 h	Daphnia magna (Big water flea)	Manufacturer			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer	SIDS IARF SIAM		
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
106-97-8	butane						, ,		
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.		
5989-27-5	(R)-p-mentha-1,8-diene; c	l-limonene							
	Acute fish toxicity	LC50	0,7 mg/l	96 h	Pimephales promelas	Manufacturer			
	Acute crustacea toxicity	EC50 mg/l	0,42	48 h	Daphnia magna	Manufacturer			

12.2. Persistence and degradability

The product has not been tested.

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 11 of 15

CAS No	Chemical name			
	Method	Value	đ	Source
	Evaluation			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexa	ane		
	OECD 301F	98 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene	4,23

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 12 of 15

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant:

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 13 of 15



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, < 5% n-hexane

14.6. Special precautions for user

Warning: Flammable gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial No information available.

emissions:

Directive 2004/42/EC on VOC in No information available.

paints and varnishes:

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation)

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

EU: European Union

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

REACh: Registration, Evaluation and Authorization of Chemicals

according to UK REACH Regulation

JMC Cockpit spray

Revision date: 13.09.2024 Page 14 of 15

UN: United Nations

PBT: Persistent, Bioaccumulative, Toxic SVHC: Substance of Very High Concern vPvB: very Persistent, very Bioaccumulative

ATE: Acute Toxicity Estimates
BCF: Bio-Concentration Factor
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration VOC: Volatile Organic Compounds

DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)

EN: European Standard

ISO: International Organization for Standardization

IUCLID: International Uniform Chemical Information Database

LC50: Lethal Concentration, 50 %

LD50: Lethal Dose, 50 % LL50: Lethal Loading, 50 %

OECD: Organisation for Economic Co-operation and Development

EC50: Effective Concentration 50 % M-Faktor: Multiplication Factor EL50: Effect Loading, 50 %

ErC50: Effective Concentration 50 %, growth rate

M-Faktor: Multiplication Factor

NOEC: No Observed Effect Concentration

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

DGR: Dangerous Goods Regulations

EmS: Emergency Schedules

IATA: International Air Transport Association

IBC: Intermediate Bulk Container

ICAO: International Civil Aviation Organization

IE: Industrial Emissions

IMDG: International Maritime Code for Dangerous Goods

LQ: Limited Quantity

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

MFAG: Medical First Aid Guide

RID: Regulations concerning the International carriage of Dangerous goods by rail

TI: Technical Instructions

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

according to UK REACH Regulation

JMC Cockpit spray Revision date: 13.09.2024 Page 15 of 15

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)