

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

JMC MoS2 rust remover

UFI: 043X-DXXN-DG04-CS3C; 8MY6-506M-Y001-SE3K

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Corrosion inhibitor

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name:	Johannes J. Matthies GmbH & Co. KG	
Street:	Hammerbrookstr. 97	
Place:	D-20097 Hamburg	
Telephone:	+ 49 (0) 40 2 37 21-0	Telefax: + 49 (0) 23 721-390
E-mail:	info@matthies.de	
Internet:	www.matthies.de	
Responsible Department:	Tel.: 040 / 23 721-0	
	Fax : 040 / 23 721-390	
	info@matthies.de	

Supplier

Company name:	Larsson UK Ltd.
Street:	7 Alpha Court, Phoenix Parkway
Place:	GB-NN17 5DP Corby
Telephone:	+ 44 1536 265633
E-mail:	info@larsson.uk.com
Internet:	www.larsson.uk.com

1.4. Emergency telephone number: + 44 1536 265633**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Aerosol 1; H222-H229
Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Signal word: Danger**Pictograms:**

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 2 of 12

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of waste according to applicable legislation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			50 - < 100 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	50 - < 100 %
	inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = > 3160 mg/kg; oral: LD50 = > 8000 mg/kg		
106-97-8	203-448-7	butane	1 - < 3 %
	inhalation: LC50 = 658 ppm (gases)		

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 3 of 12

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Causes mild skin irritation. Headache, Nausea, Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water mist. Foam, Carbon dioxide (CO₂), Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 4 of 12

6.3. Methods and material for containment and cleaning up**For containment**

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Observe instructions for use. Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Personal protection equipment: see section 8

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Observe in addition any national regulations!

Hints on joint storage

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances, Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe in addition any national regulations!

7.3. Specific end use(s)

Corrosion inhibitor

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 5 of 12

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept

Whole blood (B)

Urine (U)

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Tightly sealed safety glasses. (DIN EN 166)

Hand protection

Protect skin by using skin protective cream.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber).

Breakthrough time: 480min

Thickness of the glove material: 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus: gas filtering equipment (EN 141).

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe in addition any national regulations!

Environmental exposure controls

Observe in addition any national regulations!

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic
Odour threshold:	not determined

	Test method
pH-Value (at 20 °C):	not determined DIN 19268

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	- 11,7 °C
Flash point:	-80 °C

Flammability

Solid/liquid:	Flammable aerosol.
Lower explosion limits:	0,5 vol. %
Upper explosion limits:	11 vol. %

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 6 of 12

Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,792 g/cm ³ DIN 51757
Water solubility:	practically insoluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic:	1,3 mm ² /s
Relative vapour density:	not determined

9.2. Other information

Data apply to the technically active substance.: Relative density, Colour, Odour, Viscosity, pH

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.**Further information**

Do not mix with other chemicals.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics				
	oral	LD50 > 8000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 3160 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat	Manufacturer	
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

There are no data available on the mixture itself.

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Scenedesmus subspicatus	Manufacturer
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna (Big water flea)	Manufacturer
75-28-5	isobutane					
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Piscis	United States Environmental Protection A
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200
74-98-6	propane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	United States Environmental Protection A
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200
106-97-8	butane					
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Piscis	United States Environmental Protection A
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	US EPA OPPT Risk Assessment Division200
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
	OECD 301F	89,8 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 9 of 12

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 10 of 12

Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: -
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 11 of 12

14.6. Special precautions for user

Warning: Flammable gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions:

No information available.

Directive 2004/42/EC on VOC in paints and varnishes:

No information available.

Information according to Directive 2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

EU: European Union

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

REACH: Registration, Evaluation and Authorization of Chemicals

UN: United Nations

PBT: Persistent, Bioaccumulative, Toxic

SVHC: Substance of Very High Concern

vPvB: very Persistent, very Bioaccumulative

ATE: Acute Toxicity Estimates

BCF: Bio-Concentration Factor

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

VOC: Volatile Organic Compounds

DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)

EN: European Standard

ISO: International Organization for Standardization

IUCLID: International Uniform Chemical Information Database

LC50: Lethal Concentration, 50 %

LD50: Lethal Dose, 50 %

LL50: Lethal Loading, 50 %

OECD: Organisation for Economic Co-operation and Development

EC50: Effective Concentration 50 %

Safety Data Sheet

according to UK REACH Regulation

JMC MoS2 rust remover

Revision date: 13.09.2024

Page 12 of 12

M-Faktor: Multiplication Factor

EL50: Effect Loading, 50 %

ErC50: Effective Concentration 50 %, growth rate

M-Faktor: Multiplication Factor

NOEC: No Observed Effect Concentration

ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

DGR: Dangerous Goods Regulations

EmS: Emergency Schedules

IATA: International Air Transport Association

IBC: Intermediate Bulk Container

ICAO: International Civil Aviation Organization

IE: Industrial Emissions

IMDG: International Maritime Code for Dangerous Goods

LQ: Limited Quantity

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

MFAG: Medical First Aid Guide

RID: Regulations concerning the International carriage of Dangerous goods by rail

TI: Technical Instructions

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)