

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 1 of 16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

JMC Steinschlag-Unterbodenschutz hellgrau 500 ml

UFI: HTRT-QY9F-6G01-M4HV

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Corrosion inhibitor

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Johannes J. Matthies GmbH &amp; Co. KG

Street: Hammerbrookstr. 97

Place: D-20097 Hamburg

Telephone: + 49 (0) 40 2 37 21-0

Telefax: + 49 (0) 40 2 37 21-363

E-mail: info@matthies.de

Internet: www.matthies.de

Responsible Department: Abteilung Produktsicherheit

**Supplier**

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

Place: GB-NN17 5DP Corby

Telephone: + 44 1536 265633

E-mail: info@larsson.uk.com

Internet: www.larsson.uk.com

**1.4. Emergency telephone number:**

+ 44 1536 265633

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229

Eye Irrit. 2; H319

Skin Sens. 1; H317

STOT SE 3; H336

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

n-butyl acetate

acetone; propan-2-one; propanone

ethyl acetate

rosin; colophony

**Signal word:** Danger

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 2 of 16

**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

**Special labelling of certain mixtures**

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.  
Vapours may form explosive mixtures with air.  
Endocrine disrupting potential: none

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 3 of 16

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
123-86-4	n-butyl acetate			12,5 - < 20 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
75-28-5	isobutane			5 - < 10 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
67-64-1	acetone; propan-2-one; propanone			5 - < 10 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
106-97-8	butane			5 - < 10 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			2,5 - < 5 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
	Hydrocarbons, C9, aromatics			2,5 - < 5 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
8050-09-7	rosin; colophony			2,5 - < 5 %
	232-475-7	650-015-00-7	01-2119480418-32	
	Skin Sens. 1; H317			
1330-20-7	xylene			< 2,5 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 4 of 16

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
123-86-4	204-658-1	n-butyl acetate	12,5 - < 20 %
		inhalation: LC50 = > 21 mg/l (vapours); dermal: LD50 = > 17600 mg/kg; oral: LD50 = 10800 mg/kg	
67-64-1	200-662-2	acetone; propan-2-one; propanone	5 - < 10 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = > 15800 mg/kg; oral: LD50 = 5800 mg/kg	
141-78-6	205-500-4	ethyl acetate	5 - < 10 %
		inhalation: LC50 = 1,6 mg/l (dusts or mists); dermal: LD50 = 5620 mg/kg; oral: LD50 = > 18000 mg/kg	
	918-668-5	Hydrocarbons, C9, aromatics	2,5 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
1330-20-7	215-535-7	xylene	< 2,5 %
		inhalation: LC50 = 29 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 2000 mg/kg; oral: LD50 = 3523 mg/kg	

**Further Information**

Benzene (CAS No. 71-43-2) &lt; 0,1 % (Note P)

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. If unconscious place in recovery position and seek medical advice.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Provide fresh air. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**5.2. Special hazards arising from the substance or mixture**

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Pyrolysis products, toxic.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 5 of 16

**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use suitable breathing apparatus. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Evacuate area.

**For non-emergency personnel**

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Stop leak if safe to do so. Cover drains.

**For cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Ventilate affected area.

**Other information**

Provide adequate ventilation. Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Further information on handling**

Do not pierce or burn, even after use.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed.

Observe in addition any national regulations!

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Keep away from heat. Protect from sunlight.

**7.3. Specific end use(s)**

Corrosion inhibitor

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 6 of 16

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
-	Cycloalkanes >= C7	-	800		TWA (8 h)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL
-	Normal and branched chain alkanes >= C7 (it excludes n-heptane)	-	1200		TWA (8 h)	WEL
8050-09-7	Rosin-based solder flux fume	-	0.05		TWA (8 h)	WEL
		-	0.15		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 7 of 16

**DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
123-86-4	n-butyl acetate			
Consumer DNEL, long-term		oral	systemic	2 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	6 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	6 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	300 mg/m³
Worker DNEL, acute		inhalation	systemic	600 mg/m³
Worker DNEL, long-term		inhalation	local	300 mg/m³
Worker DNEL, acute		inhalation	local	600 mg/m³
Consumer DNEL, long-term		inhalation	systemic	35,7 mg/m³
Consumer DNEL, acute		inhalation	systemic	300 mg/m³
Consumer DNEL, long-term		inhalation	local	35,7 mg/m³
67-64-1	acetone; propan-2-one; propanone			
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Worker DNEL, acute		inhalation	local	2420 mg/m³
Worker DNEL, long-term		inhalation	systemic	1210 mg/m³
Consumer DNEL, long-term		inhalation	systemic	200 mg/m³
141-78-6	ethyl acetate			
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	734 mg/m³
Worker DNEL, acute		inhalation	systemic	1468 mg/m³
Worker DNEL, long-term		inhalation	local	734 mg/m³
Worker DNEL, acute		inhalation	local	1468 mg/m³
Consumer DNEL, long-term		inhalation	systemic	367 mg/m³
Consumer DNEL, acute		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		inhalation	local	367 mg/m³
Consumer DNEL, acute		inhalation	local	734 mg/m³
	Hydrocarbons, C9, aromatics			
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	150 mg/m³
Consumer DNEL, long-term		inhalation	systemic	32 mg/m³
1330-20-7	xylene			
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 8 of 16

Worker DNEL, long-term	inhalation	systemic	211 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	221 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	442 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	289 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	260 mg/m <sup>3</sup>
Consumer DNEL, long-term	inhalation	local	65,3 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	local	260 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
123-86-4	n-butyl acetate	
Freshwater		0,18
Marine water		0,018
Freshwater sediment		0,981
Marine sediment		0,0981
Micro-organisms in sewage treatment plants (STP)		35,6
Soil		0,0903
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

**Eye/face protection**

Suitable eye protection: Tightly sealed safety glasses.

**Hand protection**

Wear suitable gloves.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of glove material: 0,4 mm

Breakthrough time: 42 - 480 min. (Solvent)

Acetone 480 min.

n-butyl acetate 60 min.

Ethyl acetate 170 min.

Xylene 42 min.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 9 of 16

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

IF exposed: Short-term (single): Wear respiratory protection.

IF exposed: Long-term (continuous) Wear a self-contained breathing apparatus and chemical protective clothing.

Filter type: A2/P3

**Environmental exposure controls**

Avoid release to the environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid (Aerosol)
Colour:	grey
Odour:	like: Solvents
Odour threshold:	not determined
pH-Value:	not determined

**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	not determined

**Flammability**

Solid/liquid: Extremely flammable aerosol. Pressurized container: May burst if heated.

**Explosive properties**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Lower explosion limits:	(*) 1,2 vol. %
Upper explosion limits:	(**) 10,9 vol. %
Auto-ignition temperature:	(***) 365 °C
Decomposition temperature:	not determined
Vapour pressure: (at 20 °C)	3500 hPa
Density (at 20 °C):	0,8 g/cm <sup>3</sup>
Water solubility:	practically insoluble

**Solubility in other solvents**

not determined

Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic:	not determined
Relative vapour density:	not determined
Solvent content:	69,2 %: (579,1 g/l)

**9.2. Other information**

Solid content:	30,8 %
----------------	--------

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 10 of 16

(\*) n-butyl acetate

(\*\*) propane

(\*\*\*) butane

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Vapours can form explosive mixtures with air.

**10.4. Conditions to avoid**

Keep away from heat. Protect from sunlight.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Pyrolysis products, toxic.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) 48217 mg/kg; ATE (inhalation vapour) 265,2 mg/l; ATE (inhalation dust/mist) 7,595 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 10800 mg/kg	Rat	Manufacturer	OECD 401
	dermal	LD50 > 17600 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 > 21 mg/l	Rat	Manufacturer	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat		
	dermal	LD50 > 15800 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
141-78-6	ethyl acetate				
	oral	LD50 > 18000 mg/kg	Rabbit	Manufacturer	
	dermal	LD50 5620 mg/kg	Rat	Manufacturer	
	inhalation (4 h) dust/mist	LC50 1,6 mg/l	Rat	Manufacturer	
	Hydrocarbons, C9, aromatics				
	oral	LD50 > 5000 mg/kg	Rat	@0105.B000018	
	dermal	LD50 > 2000 mg/kg	Rabbit	@0105.B000018	
1330-20-7	xylene				
	oral	LD50 3523 mg/kg	Rat	@0105.B000018	
	dermal	LD50 2000 mg/kg	Rabbit	@0105.B000018	
	inhalation (4 h) vapour	LC50 29 mg/l	Rat	@0105.B000018	
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

**Sensitising effects**

May cause an allergic skin reaction. (rosin; colophony)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (n-butyl acetate)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 12 of 16

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information****12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	8300	96 h	Fisch	
	Acute algae toxicity	ErC50 mg/l	7200	96 h	Algen	
	Acute crustacea toxicity	EC50 mg/l	8450	48 h	Daphnia magna	
	Hydrocarbons, C9, aromatics					
	Acute crustacea toxicity	EC50	302 mg/l	48 h	Daphnia magna (Big water flea)	@0105.B000018
1330-20-7	xylene					
	Acute fish toxicity	LC50 mg/l	13,5	96 h	piscis	@0105.B000018
	Acute crustacea toxicity	EC50	7,4 mg/l	48 h	Daphnia magna (Big water flea)	@0105.B000018

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Collect the waste separately. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 13 of 16

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0

**Marine transport (IMDG)**

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: -  
 Special Provisions: 63 190 277 327 344 381 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 14 of 16

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, FLAMMABLE  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: &lt; 70 %

Directive 2004/42/EC on VOC in paints and varnishes: &lt; 70 %

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

**Additional information**

Aerosol directive (75/324/EEC).

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

Observe in addition any national regulations!

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

EU: European Union

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Steinschlag-Unterbodenschutz hellgrau 500 ml**

Revision date: 28.10.2024

Page 15 of 16

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 UN: United Nations  
 PBT: Persistent, Bioaccumulative, Toxic  
 SVHC: Substance of Very High Concern  
 vPvB: very Persistent, very Bioaccumulative  
 ATE: Acute Toxicity Estimates  
 BCF: Bio-Concentration Factor  
 DMEL: Derived Minimal Effect Level  
 DNEL: Derived No Effect Level  
 PNEC: Predicted No Effect Concentration  
 VOC: Volatile Organic Compounds  
 DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)  
 EN: European Standard  
 ISO: International Organization for Standardization  
 IUCLID: International Uniform Chemical Information Database  
 LC50: Lethal Concentration, 50 %  
 LD50: Lethal Dose, 50 %  
 LL50: Lethal Loading, 50 %  
 OECD: Organisation for Economic Co-operation and Development  
 EC50: Effective Concentration 50 %  
 M-Faktor: Multiplication Factor  
 EL50: Effect Loading, 50 %  
 ErC50: Effective Concentration 50 %, growth rate  
 M-Faktor: Multiplication Factor  
 NOEC: No Observed Effect Concentration  
 ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)  
 ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 DGR: Dangerous Goods Regulations  
 EmS: Emergency Schedules  
 IATA: International Air Transport Association  
 IBC: Intermediate Bulk Container  
 ICAO: International Civil Aviation Organization  
 IE: Industrial Emissions  
 IMDG: International Maritime Code for Dangerous Goods  
 LQ: Limited Quantity  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 MFAG: Medical First Aid Guide  
 RID: Regulations concerning the International carriage of Dangerous goods by rail  
 TI: Technical Instructions

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
Skin Sens. 1; H317	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H229 Pressurised container: May burst if heated.

Safety Data Sheet

according to UK REACH Regulation

JMC Steinschlag-Unterbodenschutz hellgrau 500 ml

Revision date: 28.10.2024

Page 16 of 16

H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	5	-	0	9a	7, 11	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)