

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

JMC Underbody protection wax light brown 1 ltr

UFI: 4WRT-6YYU-GG0H-9G3X

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Plating agent

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name: Johannes J. Matthies GmbH &amp; Co. KG

Street: Hammerbrookstr. 97

Place: D-20097 Hamburg

Telephone: + 49 (0) 40 2 37 21-0

Telefax: + 49 (0) 40 2 37 21-363

E-mail: info@matthies.de

Internet: www.matthies.de

Responsible Department: Abteilung Produktsicherheit

**Supplier**

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

Place: GB-NN17 5DP Corby

Telephone: + 44 1536 265633

E-mail: info@larsson.uk.com

Internet: www.larsson.uk.com

**1.4. Emergency telephone number:**

+ 44 1536 265633

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Aerosol 1; H222-H229

Skin Irrit. 2; H315

STOT SE 3; H336

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5%

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cycloalkanes, &lt;2% aromatics

**Signal word:** Danger

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 2 of 12

**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

**2.3. Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.  
 Vapours may form explosive mixtures with air.  
 Endocrine disrupting potential: none

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%			20 - < 25 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cycloalkanes, <2% aromatics			12,5 - < 20 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304 EUH066			
74-98-6	propane			12,5 - < 20 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
75-28-5	isobutane			10 - < 12,5 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
106-97-8	butane			10 - < 12,5 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 3 of 12

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%	20 - < 25 %
		inhalation: LC50 = > 25,2 mg/l (dusts or mists); dermal: LD50 = > 2920 mg/kg; oral: LD50 = > 5840 mg/kg	
	919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cycloalkanes, <2% aromatics	12,5 - < 20 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

**Further Information**

Benzene (CAS No. 71-43-2) &lt; 0,1 % (Note P)

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

**After inhalation**

Provide fresh air. If unconscious place in recovery position and seek medical advice.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

**After ingestion**

Rinse mouth immediately and drink plenty of water. Provide fresh air. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings. .

**5.2. Special hazards arising from the substance or mixture**

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

In case of fire may be liberated: Pyrolysis products, toxic.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Use suitable breathing apparatus. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Evacuate area.

**For non-emergency personnel**

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 4 of 12

**For emergency responders**

Wear personal protection equipment (refer to section 8).

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****For containment**

Stop leak if safe to do so. Cover drains.

**For cleaning up**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Ventilate affected area.

**Other information**

Provide adequate ventilation. Clean contaminated articles and floor according to the environmental legislation.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

**Advice on protection against fire and explosion**

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

**Further information on handling**

Do not pierce or burn, even after use.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed.

Observe in addition any national regulations!

**Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Keep away from heat. Protect from sunlight.

**7.3. Specific end use(s)**

Plating agent

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
-	Normal and branched chain alkanes >= C7 (it excludes n-heptane)	-	1200		TWA (8 h)	WEL

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 5 of 12

**DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%			
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes,Cycloalkanes, <2% aromatics			
Consumer DNEL, long-term		oral	systemic	125 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	208 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	125 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	871 mg/m³
Consumer DNEL, long-term		inhalation	systemic	185 mg/m³

**8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

**Protective and hygiene measures**

Remove contaminated, saturated clothing immediately. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

**Eye/face protection**

Eye protection: not required.

**Hand protection**

Wear suitable gloves.

Suitable material: Butyl caoutchouc (butyl rubber)

Thickness of glove material: 0,4 mm

Breakthrough time: 42 - 480 min. (Solvent)

Acetone 480 min.

n-butyl acetate 60 min.

Ethyl acetate 170 min.

Xylene 42 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Wear suitable protective clothing.

**Respiratory protection**

IF exposed: Short-term (single): Wear respiratory protection.

IF exposed: Long-term (continuous) Wear a self-contained breathing apparatus and chemical protective clothing.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 6 of 12

Filter type: A2/P3

**Environmental exposure controls**

Avoid release to the environment.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid (Aerosol)
Colour:	brown
Odour:	like: Solvent
Odour threshold:	not determined
pH-Value:	not determined

**Changes in the physical state**

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not applicable
Flash point:	not determined

**Flammability**

Solid/liquid:	Extremely flammable aerosol. Pressurized container: May burst if heated.
---------------	---

**Explosive properties**

Extremely flammable aerosol. Pressurized container: May burst if heated.

Lower explosion limits:	(*) 0,6 vol. %
Upper explosion limits:	(**) 10,9 vol. %
Auto-ignition temperature:	(*) > 200 °C
Decomposition temperature:	not determined
Vapour pressure: (at 20 °C)	3500 hPa
Density (at 20 °C):	0,7 g/cm <sup>3</sup>
Water solubility:	practically insoluble
<b>Solubility in other solvents</b>	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic:	not determined
Relative vapour density:	not determined
Solvent content:	81,2 % (543,4 g/l)

**9.2. Other information**

Solid content:	18,5 %
(*) Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%	
(**) propane	

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Vapours can form explosive mixtures with air.

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 7 of 12

**10.4. Conditions to avoid**

Keep away from heat. Protect from sunlight.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

In case of fire may be liberated: Pyrolysis products, toxic.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%				
	oral	LD50 > 5840 mg/kg	Rat		
	dermal	LD50 > 2920 mg/kg	Rabbit		
	inhalation (4 h) dust/mist	LC50 > 25,2 mg/l	Rat		
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cycloalkanes, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	OECD 401
	dermal	LD50 > 2000 mg/kg	Rat	Manufacturer	OECD 402

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5%; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cycloalkanes, &lt;2% aromatics)

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information**

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 8 of 12

**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%					
	Acute fish toxicity	LC50 mg/l	11,4	96 h	piscis	
	Acute algae toxicity	ErC50 mg/l	30 - 100	72 h	Algae	
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna (Big water flea)	

**12.2. Persistence and degradability**

The product has not been tested.

**12.3. Bioaccumulative potential**

The product has not been tested.

**12.4. Mobility in soil**

The product has not been tested.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No information available.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Collect the waste separately. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Dispose of waste according to applicable legislation.

**SECTION 14: Transport information****Land transport (ADR/RID)**

- 14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -



**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 9 of 12

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

**Inland waterways transport (ADN)****14.1. UN number:**

UN 1950

**14.2. UN proper shipping name:**

AEROSOLS

**14.3. Transport hazard class(es):**

2

**14.4. Packing group:**

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

**Marine transport (IMDG)****14.1. UN number:**

UN 1950

**14.2. UN proper shipping name:**

AEROSOLS

**14.3. Transport hazard class(es):**

2.1

**14.4. Packing group:**

-

Hazard label:

2.1



Marine pollutant:

-

Special Provisions:

63 190 277 327 344 381 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:**

UN 1950

**14.2. UN proper shipping name:**

AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es):**

2.1

**14.4. Packing group:**

-

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y203

Excepted quantity:

E0

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 10 of 12

IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Flammable gases.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: &lt; 85 %

Directive 2004/42/EC on VOC in paints and varnishes: &lt; 85 %

Information according to Directive 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

**Additional information**

Aerosol directive (75/324/EEC).

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

**Additional information**

Observe in addition any national regulations!

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

EU: European Union

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

REACH: Registration, Evaluation and Authorization of Chemicals

UN: United Nations

PBT: Persistent, Bioaccumulative, Toxic

SVHC: Substance of Very High Concern

vPvB: very Persistent, very Bioaccumulative

ATE: Acute Toxicity Estimates

BCF: Bio-Concentration Factor

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

VOC: Volatile Organic Compounds

DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)

EN: European Standard

**Safety Data Sheet**

according to UK REACH Regulation

**JMC Underbody protection wax light brown 1 ltr**

Revision date: 28.10.2024

Page 11 of 12

ISO: International Organization for Standardization  
 IUCLID: International Uniform Chemical Information Database  
 LC50: Lethal Concentration, 50 %  
 LD50: Lethal Dose, 50 %  
 LL50: Lethal Loading, 50 %  
 OECD: Organisation for Economic Co-operation and Development  
 EC50: Effective Concentration 50 %  
 M-Faktor: Multiplication Factor  
 EL50: Effect Loading, 50 %  
 ErC50: Effective Concentration 50 %, growth rate  
 M-Faktor: Multiplication Factor  
 NOEC: No Observed Effect Concentration  
 ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)  
 ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 DGR: Dangerous Goods Regulations  
 EmS: Emergency Schedules  
 IATA: International Air Transport Association  
 IBC: Intermediate Bulk Container  
 ICAO: International Civil Aviation Organization  
 IE: Industrial Emissions  
 IMDG: International Maritime Code for Dangerous Goods  
 LQ: Limited Quantity  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 MFAG: Medical First Aid Guide  
 RID: Regulations concerning the International carriage of Dangerous goods by rail  
 TI: Technical Instructions

**Classification for mixtures and used evaluation method according to GB CLP Regulation**

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Skin Irrit. 2; H315	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.  
 H222 Extremely flammable aerosol.  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H229 Pressurised container: May burst if heated.  
 H280 Contains gas under pressure; may explode if heated.  
 H304 May be fatal if swallowed and enters airways.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to UK REACH Regulation

JMC Underbody protection wax light brown 1 ltr

Revision date: 28.10.2024

Page 12 of 12

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	5	-	0	9a	7, 11	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)