



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 17

SDS No. : 77169
V005.0

TEROSON WT S3000 LT

Revision: 14.01.2020
printing date: 15.01.2020
Replaces version from: 28.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON WT S3000 LT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Underbody coating

1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 211 797 0

Fax-no.: +49 211 798 2009

ua-productsafety.de@henkel.com

1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no. +49-(0)211-797-3350 for exceptional cases.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

1,2-Benzisothiazol-3(2H)-one

2-Octyl-2H-isothiazol-3-one
2-methylisothiazol-3(2H)-one

Signal word: Warning

Hazard statement: H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statement: P261 Avoid breathing mist/spray.
Prevention P280 Wear protective gloves/eye protection.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Composition

Base substances of preparation:

Styrene-acrylate copolymer

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
ammonia, aqueous solution 1336-21-6	215-647-6 01-2119488876-14	0,25- < 2,5 %	Met. Corr. 1 H290 Skin Corr. 1B H314 Aquatic Acute 1 H400 Aquatic Chronic 2 H411 Eye Dam. 1 H318 STOT SE 3 H335 Acute Tox. 4 H302
1,2-Benzisothiazol-3(2H)-one 2634-33-5	220-120-9 01-2120761540-60	0,005- < 0,05 % (50 ppm- < 500 ppm)	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Acute Tox. 4 H302 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Dam. 1 H318 Acute Tox. 2 H330
2-Octyl-2H-isothiazol-3-one 26530-20-1	247-761-7	0,005- < 0,05 % (50 ppm- < 500 ppm)	Acute Tox. 3; Inhalation H331 Acute Tox. 3; Dermal H311 Skin Corr. 1B H314 Skin Sens. 1 H317 Aquatic Acute 1 H400 Acute Tox. 4; Oral H302 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10
2-methylisothiazol-3(2H)-one 2682-20-4	220-239-6 01-2120764690-50	0,0015- < 0,015 % (15 ppm- < 150 ppm)	Aquatic Chronic 1 H410 Skin Sens. 1A H317 Acute Tox. 2; Inhalation H330 Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Eye Dam. 1 H318 Aquatic Acute 1 H400 Skin Corr. 1B H314 M factor (Acute Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

- Do not eat, drink or smoke while working.
- Wash hands before work breaks and after finishing work.
- Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Frost-sensitive

Ensure good ventilation/extraction.

Store in a cool, frost-free place.

Temperatures between + 10 °C and + 25 °C

7.3. Specific end use(s)

Underbody coating

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Germany

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
2-(2-Butoxyethoxy)ethyl acetate 124-17-4	10	67	Exposure limit(s):	1.5 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
2-(2-Butoxyethoxy)ethyl acetate 124-17-4			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900
2-Octyl-2H-isothiazol-3-one 26530-20-1			Skin designation:	Can be absorbed through the skin.	TRGS 900
2-Octyl-2H-isothiazol-3-one 26530-20-1		0,05	Exposure limit(s):	2 If the AGW and BGW values are complied with, there should be no risk of reproductive damage (see Number 2.7).	TRGS 900
2-Octyl-2H-isothiazol-3-one 26530-20-1			Short Term Exposure Classification:	Category I: substances for which the localized effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages.	TRGS 900

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
ammonia, aqueous solution 1336-21-6	aqua (freshwater)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (marine water)		0,001 mg/l				
ammonia, aqueous solution 1336-21-6	aqua (intermittent releases)		0,0068 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (freshwater)		0,00403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (marine water)		0,000403 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	aqua (intermittent releases)		0,0011 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sewage treatment plant (STP)		1,03 mg/l				
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (freshwater)				0,0499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	sediment (marine water)				0,00499 mg/kg		
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Soil				3 mg/kg		
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (freshwater)		0,0039 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (marine water)		0,0039 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	sewage treatment plant (STP)		0,23 mg/l				
2-methylisothiazol-3(2H)-one 2682-20-4	Soil				0,047 mg/kg		
2-methylisothiazol-3(2H)-one 2682-20-4	aqua (intermittent releases)		0,0039 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
ammonia, aqueous solution 1336-21-6	Workers	dermal	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	dermal	Long term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Acute/short term exposure - local effects		36 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - systemic effects		47,6 mg/m3	
ammonia, aqueous solution 1336-21-6	Workers	Inhalation	Long term exposure - local effects		14 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	dermal	Acute/short term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	dermal	Long term exposure - systemic effects		68 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - systemic effects		23,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Acute/short term exposure - local effects		7,2 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - systemic effects		23,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	Inhalation	Long term exposure - local effects		2,8 mg/m3	
ammonia, aqueous solution 1336-21-6	General population	oral	Acute/short term exposure - systemic effects		6,8 mg/kg	
ammonia, aqueous solution 1336-21-6	General population	oral	Long term exposure - systemic effects		6,8 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	inhalation	Long term exposure - systemic effects		6,81 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Workers	dermal	Long term exposure - systemic effects		0,966 mg/kg	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	inhalation	Long term exposure - systemic effects		1,2 mg/m3	
1,2-Benzisothiazol-3(2H)-one 2634-33-5	General population	dermal	Long term exposure - systemic effects		0,345 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Long term exposure - local effects		0,021 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	Workers	inhalation	Acute/short term exposure - local effects		0,043 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Long term exposure - local effects		0,021 mg/m3	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Long term exposure - systemic effects		0,027 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	oral	Acute/short term exposure - systemic effects		0,053 mg/kg	
2-methylisothiazol-3(2H)-one 2682-20-4	General population	inhalation	Acute/short term exposure - local		0,043 mg/m3	

		effects			
--	--	---------	--	--	--

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway).

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties
--

9.1. Information on basic physical and chemical properties

Appearance	liquid
	liquid
	light
Odor	of amine
Odour threshold	No data available / Not applicable
pH	8,0
(20 °C (68 °F))	
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 130 °C (> 266 °F); ASTM D3278
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable

Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,25 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Miscible
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (; 20 °C (68 °F))	400 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable
Solid content (120 °C)	70 %

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
ammonia, aqueous solution 1336-21-6	LD50	350 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	LD50	490 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2-methylisothiazol-3(2H)- one 2682-20-4	LD50	120 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2-Octyl-2H-isothiazol-3-one 26530-20-1	LD50	311 mg/kg	rabbit	not specified
2-methylisothiazol-3(2H)-one 2682-20-4	LD50	242 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	0,4 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
2-Octyl-2H-isothiazol-3-one 26530-20-1	LC50	0,58 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	0,11 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	moderately irritating	4 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
2-methylisothiazol-3(2H)-one 2682-20-4	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	corrosive			not specified
1,2-Benzisothiazol-3(2H)-one 2634-33-5	corrosive	3 h	rabbit	EPA OPP 81-4 (Acute Eye Irritation)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
ammonia, aqueous solution 1336-21-6	not sensitising	not specified	guinea pig	not specified
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-Octyl-2H-isothiazol-3- one 26530-20-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2-methylisothiazol-3(2H)- one 2682-20-4	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	negative	bacterial reverse mutation assay (e.g Ames test)	not specified		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
ammonia, aqueous solution 1336-21-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	negative	oral: unspecified		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-methylisothiazol-3(2H)- one 2682-20-4	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
ammonia, aqueous solution 1336-21-6	not carcinogenic	oral: feed	104 w daily	rat		OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
ammonia, aqueous solution 1336-21-6	NOAEL P 408 mg/kg	screening	oral: unspecified	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL P 112 mg/kg NOAEL F1 56,6 mg/kg NOAEL F2 56,6 mg/kg	Two generation study	oral: feed	rat	EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
2-methylisothiazol-3(2H)- one 2682-20-4	NOAEL P 200 ppm NOAEL F1 200 ppm NOAEL F2 200 ppm	Two generation study	oral: drinking water	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 150 mg/kg	oral: gavage	28 days daily	rat	OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
1,2-Benzisothiazol-3(2H)- one 2634-33-5	NOAEL 69 mg/kg	oral: feed	90 days daily	rat	EPA OPP 82-1 (90-Day Oral Toxicity)
2-methylisothiazol-3(2H)- one 2682-20-4	NOAEL 60 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	LC50	0,16 - 1,1 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
ammonia, aqueous solution 1336-21-6	NOEC	< 0,048 mg/l	31 d	Channel catfish	OECD Guideline 215 (Fish, Juvenile Growth Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50	2,15 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,21 mg/l	30 d	Oncorhynchus mykiss	OECD Guideline 215 (Fish, Juvenile Growth Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	LC50	0,036 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,022 mg/l	21 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early life stage toxicity test)
2-methylisothiazol-3(2H)-one 2682-20-4	LC50	4,77 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	EC50	25,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	2,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,42 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,93 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	NOEC	0,79 mg/l	96 h	Daphnia magna	EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	1,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,0016 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,04 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
ammonia, aqueous solution 1336-21-6	EC50	> 1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
ammonia, aqueous solution 1336-21-6	NOEC	1.000 mg/l	72 h	Skeletonema costatum	ISO 10253 (Water quality)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	0,11 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	NOEC	0,0403 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	EC50	0,084 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	NOEC	0,004 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	NOEC	0,03 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC50	0,22 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50	23 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2-methylisothiazol-3(2H)-one 2682-20-4	EC 50	41 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	not readily biodegradable.	aerobic	42,1 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-Octyl-2H-isothiazol-3-one 26530-20-1	readily biodegradable	aerobic	> 83 %	28 d	OECD Guideline 303 A (Simulation Test Aerobic Sewage Treatment, A: Activated Sludge Units)
2-methylisothiazol-3(2H)-one 2682-20-4	inherently biodegradable	aerobic	97 %	48 h	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
2-methylisothiazol-3(2H)-one 2682-20-4	readily biodegradable	aerobic	> 70 %	28 d	OECD Guideline 309 (Aerobic Mineralisation in Surface Water Simulation Biodegradation Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	6,62	56 day		not specified	other guideline:

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
ammonia, aqueous solution 1336-21-6	-1,14		EU Method A.8 (Partition Coefficient)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	0,7	20 °C	EU Method A.8 (Partition Coefficient)
2-Octyl-2H-isothiazol-3-one 26530-20-1	2,9		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-methylisothiazol-3(2H)-one 2682-20-4	-0,5		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
ammonia, aqueous solution 1336-21-6	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-Octyl-2H-isothiazol-3-one 26530-20-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-methylisothiazol-3(2H)-one 2682-20-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

- 14.1. UN number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 0 %
(VOCV 814.018 VOC regulation
CH)

VOC Paints and Varnishes (EU):

Product (sub)category: This product is not a subject of the Directive 2004/42/EC

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Germany):

WGK: WGK = 1, slightly water endangering mixture. Classification according to the mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April 2017.

Storage class according to TRGS 510: 10

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H290 May be corrosive to metals.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.