Safety Data Sheet

according to UK REACH Regulation

JMC Jump start spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC Jump start spray

UFI: K3WM-3155-MH09-0VDM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Fuel

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name:	Johannes J. Matthies GmbH & Co. KG	
Street:	Hammerbrookstr. 97	
Place:	D-20097 Hamburg	
Telephone:	+ 49 (0) 40 2 37 21-0	Telefax: + 49 (0) 40 2 37 21-363
E-mail:	info@matthies.de	
Internet:	www.matthies.de	
Responsible Department:	Abteilung Produktsicherheit	

Supplier

Company name:	Larsson UK Ltd.
Street:	7 Alpha Court, Phoenix Parkway
Place:	GB-NN17 5DP Corby
Telephone:	+ 44 1536 265633
E-mail:	info@larsson.uk.com
Internet:	www.larsson.uk.com

1.4. Emergency telephone number:

+ 44 1536 265633

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

acetone; propan-2-one; propanone
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane
Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics

Signal word: Danger

Pictograms:

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe Aerosol.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of Water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.
The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied gas; H220 H280			
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane			20 - < 25 %
	216-653-1	603-181-00-X		
	Flam. Liq. 2, Skin Irrit. 2; H225 H315			
67-64-1	acetone; propan-2-one; propanone			5 - < 10 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			5 - < 10 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			5 - < 10 %
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-56-1	methanol			0,1 - < 1 %
	200-659-6	603-001-00-X		
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
1634-04-4	216-653-1	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	20 - < 25 %
	inhalation: LC50 = 85 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3866 mg/kg		
67-64-1	200-662-2	acetone; propan-2-one; propanone	5 - < 10 %
	inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg		
	921-024-6	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	5 - < 10 %
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg		
64742-49-0	927-510-4	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics	5 - < 10 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = 5500 mg/kg		
106-97-8	203-448-7	butane	1 - < 3 %
	inhalation: LC50 = 658 ppm (gases)		
67-56-1	200-659-6	methanol	0,1 - < 1 %
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: LD50 = 17100 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. When in doubt or if symptoms are observed, get medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. When in doubt or if symptoms are observed, get medical advice.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause drowsiness or dizziness.
Headache, Nausea, Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist. Foam, Carbon dioxide (CO2), Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Use personal protection equipment.

For non-emergency personnel

First aider: Pay attention to self-protection!

For emergency responders

Fight fire with normal precautions from a reasonable distance.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.
Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.
When using do not eat, drink, smoke, sniff.
Personal protection equipment: see section 8
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe in addition any national regulations!

Hints on joint storage

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances, Food and feedingstuffs

Further information on storage conditions

Protect against: Frost. Protect against direct sunlight. Store in a cool dry place. Observe in addition any national regulations!

7.3. Specific end use(s)

Fuel

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
1634-04-4	Methyl-tert-butyl ether	50	183.5		TWA (8 h)	WEL
		100	367		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics			
Worker DNEL, long-term		inhalation	systemic	2085 mg/m³
Worker DNEL, long-term		dermal	systemic	300 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³
Consumer DNEL, long-term		dermal	systemic	149 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	149 mg/kg bw/day

Additional advice on limit values

a no restriction
b End of exposure or end of shift
c at long term exposure: after several previous shifts
d before next shift

Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept
Z: A risk of reproductive effects cannot to be excluded if the occupational exposure limit value (AGW) and the biological limit value (BGW) is kept
Whole blood (B)
Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Tightly sealed safety glasses. (DIN EN 166)

Hand protection

Protect skin by using skin protective cream.
When handling with chemical substances, protective gloves must be worn with the CE-label including the four

control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Suitable material: NBR (Nitrile rubber).
Breakthrough time: 480 min
Thickness of the glove material: 0,45 mm
EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Respiratory protection necessary at: exceeding exposure limit values
Suitable respiratory protection apparatus: gas filtering equipment (EN 141).
Filtering device with filter or ventilator filtering device of type: AX
Observe the wear time limits as specified by the manufacturer.
Observe in addition any national regulations!

Environmental exposure controls

Avoid release to the environment.
Observe in addition any national regulations!

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	like: Solvent
Odour threshold:	not determined

		Test method
pH-Value (at 20 °C):	not determined	DIN 19268
Changes in the physical state		
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	-42 °C	
Flash point:	-80 °C	
Flammability		
Solid/liquid:	Flammable aerosol.	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	14,3 vol. %	
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,7429 g/cm³	DIN 51757
Water solubility:	practically insoluble	

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic:	not determined
Relative vapour density:	not determined

9.2. Other information

Data apply to the technically active substance.:Relative density, Colour, Odour, Viscosity, pH

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable, Ignition hazard.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO_2), Carbon monoxide, aldehydes, carbon black, Pyrolysis products, toxic.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 8790 mg/kg; ATE (dermal) 26370 mg/kg; ATE (inhalation vapour) 263,7 mg/l; ATE (inhalation dust/mist) 43,95 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane				
	oral	LD50 3866 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2000 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 85 mg/l	Rat	Manufacturer	
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 5800 mg/kg	Rat	Manufacturer	
	dermal	LD50 20000 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat	Manufacturer	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane				
	oral	LD50 > 5000 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat	Manufacturer	
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics				
	oral	LD50 5500 mg/kg	Rat	Manufacturer	
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Manufacturer	
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Manufacturer	OECD 403
106-97-8	butane				
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS	
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Affe	Manufacturer	
	dermal	LD50 17100 mg/kg	Rabbit	Manufacturer	
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Manufacturer	Study report (1980)
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.
No indication of human carcinogenicity.
No indications of human germ cell mutagenicity exist.
No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] | [d]	Species	Source	Method
75-28-5	isobutane						
	Acute fish toxicity	LC50	91,42 mg/l	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane						
	Acute fish toxicity	LC50	672 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer	
	Acute algae toxicity	ErC50	> 800 mg/l	72 h	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50	651 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	
67-64-1	acetone; propan-2-one; propanone						
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss	Manufacturer	
	Acute algae toxicity	ErC50	5000 mg/l	96 h	Desmodesmus subspicatus	Manufacturer	
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna	Manufacturer	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane						
	Acute fish toxicity	LC50	> 1 - 10 mg/l	96 h	Pimephales promelas (fathead minnow)	Manufacturer	
	Acute algae toxicity	ErC50	10 - 30 mg/l	72 h	Pseudokirchneriella subcapitata	Manufacturer	OECD 201
	Acute crustacea toxicity	EC50	> 1 - 10 mg/l	48 h	Daphnia magna	Manufacturer	
74-98-6	propane						
	Acute fish toxicity	LC50	49,9 mg/l	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50	19,37 mg/l	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50	69,43 mg/l	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
64742-49-0	Hydrocabons, C7, n-alkanes, iso-alkanes, cyclics						
	Acute fish toxicity	LL50	> 13,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	Manufacturer (Study report(1995))	OECD 201
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	Manufacturer	SIDS IARF SIAM
	Acute crustacea toxicity	EC50	> 1 - 10 mg/l	48 h	Daphnia magna (Big water flea)	Manufacturer	
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer	SIDS IARF SIAM
106-97-8	butane						

	Acute fish toxicity	LC50 49,9 mg/l	96 h	Piscis	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 19,37 mg/l	96 h	Algae	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 69,43 mg/l	48 h	Daphnia sp.	US EPA OPPT Risk Assessment Division200	Calculation using ECOSAR Program v1.00.
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	
	Acute algae toxicity	ErC50 ca. 220000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna (Big water flea)	Water Research 23(4): 495-499 (1989)	
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas (fathead minnow)	Manufacturer	SAR and QSAR in Environmental Research
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna (Big water flea)	Manufacturer	OECD QSAR Toolbox Report (2013)

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane			
	OECD 301B	2 %	28	Manufacturer
	Not readily biodegradable (according to OECD criteria)			
67-64-1	acetone; propan-2-one; propanone			
	OECD 301B	90,9 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane			
	OECD 301F	98 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			
67-56-1	methanol			
	OECD 301E	98 %	28	Manufacturer
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
1634-04-4	tert-butyl methyl ether; MTBE; 2-methoxy-2-methylpropane	0,94
67-64-1	acetone; propan-2-one; propanone	-0,24
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, < 5% hexane	3,4 - 5,2
74-98-6	propane	1,09
106-97-8	butane	1,09
67-56-1	methanol	-0,77

BCF

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio (Common Carp)	Comparative Biochemi

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Transport category:	2
Tunnel restriction code:	D

Inland waterways transport (ADN)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0

Marine transport (IMDG)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2, see SP63
Marine pollutant:	-
Special Provisions:	63, 190, 277, 327, 344, 959
Limited quantity:	See SP277
Excepted quantity:	E0
EmS:	F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1

Special Provisions:	A145 A167 A802
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Directive 2010/75/EU on industrial emissions:	No information available.
Directive 2004/42/EC on VOC in paints and varnishes:	No information available.
Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS

Additional information

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging
EU: European Union
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
REACh: Registration, Evaluation and Authorization of Chemicals
UN: United Nations
PBT: Persistent, Bioaccumulative, Toxic
SVHC: Substance of Very High Concern
vPvB: very Persistent, very Bioaccumulative
ATE: Acute Toxicity Estimates
BCF: Bio-Concentration Factor
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
VOC: Volatile Organic Compounds
DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)
EN: European Standard
ISO: International Organization for Standardization
IUCLID: International Uniform ChemicaL Information Database
LC50: Lethal Concentration, 50 %
LD50: Lethal Dose, 50 %
LL50: Lethal Loading, 50 %
OECD: Organisation for Economic Co-operation and Development
EC50: Effective Concentration 50 %
M-Faktor: Multiplication Factor
EL50: Effect Loading, 50 %

ErC50: Effective Concentration 50 %, growth rate
M-Faktor: Multiplication Factor
NOEC: No Observed Effect Concentration
ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
DGR: Dangerous Goods Regulations
EmS: Emergency Schedules
IATA: International Air Transport Association
IBC: Intermediate Bulk Container
ICAO: International Civil Aviation Organization
IE: Industrial Emissions
IMDG: International Maritime Code for Dangerous Goods
LQ: Limited Quantity
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
MFAG: Medical First Aid Guide
RID: Regulations concerning the International carriage of Dangerous goods by rail
TI: Technical Instructions

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)