



according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5I

Print date: 10.07.2020 Product code: 5580056 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC Getriebeöl ATF CVT Extra 5l

Further trade names

JMC Getriebeöl ATF CVT Extra 1I (JM-Nr. 558 00 53) JMC Getriebeöl ATF CVT Extra 20I (JM-Nr. 558 00 54) JMC Getriebeöl ATF CVT Extra 60I (JM-Nr. 558 00 71)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ATF

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Johannes J. Matthies GmbH & Co. KG

Street: Hammerbrookstr. 97
Place: D-20097 Hamburg
Telephone: + 49 (0) 40 2 37 21-0
e-mail: info@matthies.de
Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

 Place:
 GB-NN17 5DP Corby

 Telephone:
 + 44 1536 265633

 e-mail:
 info@larsson.uk.com

 Internet:
 www.larsson.uk.com

 1.4. Emergency telephone
 + 44 1536 265633

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 2 of 8

Hazardous components

| CAS No | Chemical name | | | |
|------------|---------------------------------------|--------------|------------------|--|
| | EC No | Index No | REACH No | |
| | GHS Classification | | • | |
| 64742-54-7 | Distillates (petroleum), hydrotreate | ied | 60 - <= 100 % | |
| | 265-157-1 | 649-467-00-8 | 01-2119484627-25 | |
| | Asp. Tox. 1; H304 | | | |
| | Methacrylatcopolymer | | 5 - < 15 % | |
| | | | | |
| | Eye Irrit. 2; H319 | • | | |
| 72623-86-0 | Baseoil - unspecified, Lubricating of | 2,5 - < 5 % | | |
| | 276-737-9 | 649-482-00-X | 01-2119474878-16 | |
| | Asp. Tox. 1; H304 | | | |
| 64742-55-8 | Distillates (petroleum), hydrotreate | 2,5 - < 5 % | | |
| | 265-158-7 | 649-468-00-3 | 01-2119487077-29 | |
| | Asp. Tox. 1; H304 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

Immediately remove any contaminated clothing, shoes or stockings. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Provide fresh air. In case of inhalation of aerosols/spray/spray droplets: Consult a physician. Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings. Carbon dioxide (CO2). Dry extinguishing powder. Foam.

Unsuitable extinguishing media

Strong water jet

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 3 of 8

5.2. Special hazards arising from the substance or mixture

Non-flammable. Particular hazard due to substance itself, its combustion products or resulting gases: Carbon dioxide (CO2). Carbon monoxide. Sulphur oxides. Phosphorus oxides. Hydrogen sulphide (H2S).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

carbon black In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Dispose of waste according to applicable legislation. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Special danger of slipping by leaking/spilling product. Wear suitable protective clothing. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Apply skin protection cream for preventive skin protection. Wash hands before breaks and after work.

Conditions to avoid: aerosol or mist formation

Advice on protection against fire and explosion

No special fire protection measures are necessary.

When using do not smoke.

Fire class: B (DIN-/EN-Norms: EN2)

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep away from heat. Keep/Store only in original container.

Hints on joint storage

Do not store together with: Food and feedingstuffs, Oxidizing agent

Further information on storage conditions

If product enters soil, it will be mobile and may contaminate groundwater.

7.3. Specific end use(s)

ATF

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 4 of 8



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Apply skin protection cream for preventive skin protection. Keep away from food, drink and animal feedingstuffs. Do not breathe vapour.

Eye/face protection

In fine dispersion/spraying/misting: Wear eye protection/face protection.

Hand protection

Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

In fine dispersion/spraying/misting: Wear protective gloves and protective clothing.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: amber
Odour: characteristic

Test method

pH-Value: not applicable DIN 51369

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

not determined
not determined

Pour point: approx. -39 °C DIN ISO 3016
Flash point: > 227 °C ISO 2592

Flammability

Solid: not applicable
Gas: not applicable

Explosive properties

The product is not explosive.

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

not determined

not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 5 of 8

Oxidizing properties

Not oxidising.

Vapour pressure: < 0,1 hPa calculated.

(at 20 °C)

Density (at 15 °C): 0,85 g/cm³ DIN 51757

Water solubility: practically insoluble

(at 20 °C)

Solubility in other solvents

Soluble in hydrocarbons. (Mineral oil)

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: ~7,5 mm²/s DIN 51562

(at 100 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Odour threshold: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

No thermal decomposition if stored/handled/transported properly. (> 100 $^{\circ}$ C).

10.3. Possibility of hazardous reactions

Reactions possible with oxidising agents.

10.4. Conditions to avoid

Oxidising agent, strong

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

none

Further information

No thermal decomposition if stored/handled/transported properly.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 6 of 8

| CAS No | Chemical name | | | | |
|------------|---|------|--------------|---------|--------------|
| | Exposure route | Dose | | Species | Source |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified | | | | |
| | oral | LD50 | > 2000 mg/kg | Rat | Manufacturer |
| | dermal | LD50 | > 2000 mg/kg | Rabbit | Manufacturer |
| | inhalation (4 h) vapour | LC50 | > 5000 mg/l | Rat | Manufacturer |
| 64742-55-8 | Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified | | | | |
| | oral | LD50 | > 5000 mg/kg | Rat | Manufacturer |
| | dermal | LD50 | > 3000 mg/kg | Rabbit | Manufacturer |

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Frequently or prolonged contact with skin may cause dermal irritation.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Other observations

Has degreasing effect on the skin.

Further information

No special hazards caused by the product are known if it is used as intended and instructions given on precautionary measures are observed.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

| CAS No | Chemical name | | | | | |
|------------|---|------|-------------|-----------|---------|--------------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified | | | | | |
| | Acute fish toxicity | LC50 | > 1000 mg/l | 96 h | Piscis | Manufacturer |
| | Acute crustacea toxicity | EC50 | >100 mg/l | 48 h | Daphnia | Manufacturer |

12.2. Persistence and degradability

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants. Poorly eliminated from water. Not readily biodegradable (according to OECD criteria). Product is partially biodegradable. Significant residues remain.

Waste oils should not be discharged into the sewage system or bodies of water, nor should they be allowed to seep into soil.

12.3. Bioaccumulative potential

The product has not been tested. Do not allow uncontrolled discharge of product into the environment.

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---|---------|
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified | > 4 |

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 7 of 8

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The specified waste codes are recommended due to the intended use of the product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Dispose of this material and its container to hazardous or special waste collection point. Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Inland waterways transport (ADN)

| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Marine transport (IMDG)

| , | |
|-----------------------------------|--|
| 14.1. UN number: | No dangerous good in sense of this transport regulation. |
| 14.2. UN proper shipping name: | No dangerous good in sense of this transport regulation. |
| 14.3. Transport hazard class(es): | No dangerous good in sense of this transport regulation. |
| 14.4. Packing group: | No dangerous good in sense of this transport regulation. |

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.

according to Regulation (EC) No 1907/2006

JMC Getriebeöl ATF CVT Extra 5l

Print date: 10.07.2020 Product code: 5580056 Page 8 of 8

14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration. 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)