



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_DE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ GEAR OIL 75W90
SYNTHETIC BLEND GEAR OIL

Product code : 867064

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Gear and lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 0 30-1
92 40

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

P102	container or label at hand.
P103	Keep out of reach of children.
Prevention:	Read carefully and follow all instructions.
P273	Avoid release to the environment.
Disposal:	
P501	Dispose of contents/ container to an approved waste disposal plant.

Additional Labelling:

EUH208 Contains Alkylamine trialkyldithiophosphate phosphate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 70,00 - < 80,00
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	Asp. Tox.1; H304	>= 2,50 - < 5,00
Alkylamine trialkyldithiophosphate phosphate		Acute Tox.4; H302 Eye Dam.1; H318 Skin Sens.1B; H317 Aquatic Chronic2; H411	>= 0,50 - < 1,00
(Z)-Octadec-9-enylamine	112-90-3 204-015-5	Acute Tox.4; H302 Skin Corr.1B; H314 Eye Dam.1; H318 STOT SE3; H335 STOT RE2; H373	>= 0,10 - < 0,25



SAFETY DATA SHEET
 Valvoline™ GEAR OIL 75W90 SYNTHETIC
 BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

		STOT RE2; H373 Asp. Tox.1; H304 Aquatic Acute1; H400 Aquatic Chronic1; H410	
Substances with a workplace exposure limit :			
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7 01-2119484627-25-xxxx		>= 1,00 - < 2,50
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0 265-169-7 01-2119471299-27-xxxx		>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Smoking, eating and drinking should be prohibited in the
application area.
For personal protection see section 8.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and
kept upright to prevent leakage.

Advice on common storage : No materials to be especially mentioned.

Storage class (TRGS 510) : 10, Combustible liquids

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection



SAFETY DATA SHEET
 Valvoline™ GEAR OIL 75W90 SYNTHETIC
 BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9, 64742-56-9	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : Nitrile rubber butyl-rubber

Skin and body protection : Wear as appropriate:
Safety shoes

Respiratory protection : No personal respiratory protective equipment normally required.

No personal respiratory protective equipment normally required.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
pH	:	Not applicable
Pour point	:	< -42 °C
Boiling point/boiling range	:	No data available No data available
Flash point	:	214 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0,877 g/cm ³
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 98 mm²/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Species: Rabbit

Result: Slight, transient irritation

OLEYLAMINE:

Result: Corrosive after 3 minutes to 1 hour of exposure

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Species: Rabbit

Result: Slight, transient irritation

Alkylamine trialkyldithiophosphate phosphate:

Result: Corrosive

OLEYLAMINE:

Result: Corrosive



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

HEAVY PARAFFINIC DISTILLATE:

Result: **No eye irritation**

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: **Slight, transient irritation**

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Test Type: **Buehler Test**

Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

Method: **OECD Test Guideline 406**

Alkylamine trialkyldithiophosphate phosphate:

Assessment: **The product is a skin sensitiser, sub-category 1B.**

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: **Buehler Test**

Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

STOT - repeated exposure

Not classified based on available information.

Components:

OLEYLAMINE:

Target Organs: **Gastro-intestinal system, Liver, Immune system**
Assessment: **The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.**

Aspiration toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

OLEYLAMINE:

May be fatal if swallowed and enters airways.

HEAVY PARAFFINIC DISTILLATE:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : **LL50 (Fish): > 100 mg/l**
Exposure time: **96 h**

Toxicity to daphnia and other : **EL50 (Aquatic invertebrates): > 10.000 mg/l**



SAFETY DATA SHEET
 Valvoline™ GEAR OIL 75W90 SYNTHETIC
 BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

aquatic invertebrates	Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Species: Aquatic invertebrates

Distillates (petroleum), solvent-dewaxed light paraffinic	
Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211

Alkylamine trialkyldithiophosphate phosphate Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Toxic to aquatic life.
Long-term (chronic) aquatic hazard	: Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

(Z)-Octadec-9-enylamine

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 0,11 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0,011 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): 0,083 mg/l Exposure time: 72 h Remarks: Information given is based on data obtained from similar substances. NOEC (Pseudokirchneriella subcapitata (green algae)): 0,01 mg/l Exposure time: 96 h
M-Factor (Short-term (acute) aquatic hazard)	: 10
M-Factor (Long-term (chronic) aquatic hazard)	: 10

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10.000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Species: Aquatic invertebrates

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
------------------	---



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

	Exposure time: 96 h
	Test Type: static test
	Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l
	Exposure time: 48 h
	Test Type: static test
	Test substance: WAF
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (algae)): >= 100 mg/l
	End point: Growth inhibition
	Exposure time: 72 h
	Test Type: static test
	Test substance: WAF

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.

12.2 Persistence and degradability

Components:

Distillates (petroleum), solvent-dewaxed light paraffinic

Biodegradability	: Result: Inherently biodegradable
	Biodegradation: 31 %
	Exposure time: 28 d
	Method: OECD Test Guideline 301B

(Z)-Octadec-9-enylamine

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 44 %
	Exposure time: 28 d

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Biodegradability	: Result: Inherently biodegradable
	Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

(Z)-Octadec-9-enylamine

Bioaccumulation	: Species: Fish
	Bioconcentration factor (BCF): > 500



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Partition coefficient: n-octanol/water : log Pow: **estimated > 4**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Partition coefficient: n-octanol/water : log Pow: **Expected > 7**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified (Number on list **28**)
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM) (Number on list **28**)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (Number on list **28**)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (Number on list **28**)

(Number on list **28**)

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germany) : WGK 3 highly hazardous to water

TA Luft List (Germany) : Total dust:
Not applicable
Inorganic substances in powdered form:
Not applicable
Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
portion Class 1: 8,05 %

Carcinogenic substances:
portion Class 3: 11,72 %

Mutagenic:
Not applicable
Toxic to reproduction:
Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
TCSI	:	Not in compliance with the inventory
TSCA	:	On TSCA Inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000221054

Full text of H-Statements

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average



SAFETY DATA SHEET
Valvoline™ GEAR OIL 75W90 SYNTHETIC
BLEND GEAR OIL

Version: 5.0

Revision Date: 14.09.2021

Print Date: 28/12/2021

vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class