



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_DE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ ALL CLIMATE 15W40 Motor Oil

Product code : 872784

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 0 30-1
92 40

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 01-2119487077-29-xxxx	Asp. Tox.1; H304	>= 2,50 - < 5,00
Zinc alkyldithiophosphate	68649-42-3 272-028-3 01-2119493635-27-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50
CALCIUM LONG- CHAIN ALKYLPHENATE SULFIDE	122384-87-6	Aquatic Chronic4; H413	>= 1,00 - < 2,50
Substances with a workplace exposure limit :			
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		>= 70,00 - < 80,00
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7 01-2119484627-25-xxxx		>= 5,00 - < 10,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Wash contaminated clothing before re-use. If on skin, rinse well with water. Remove contaminated clothing. If irritation develops, get medical attention.
In case of eye contact	: If eye irritation persists, consult a specialist. Protect unharmed eye. Remove contact lenses. Flush eyes with water as a precaution.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No symptoms known or expected.
----------	----------------------------------

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: No hazards which require special first aid measures.
-----------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
--------------------------------------	---



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Avoid contact with skin and eyes.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not smoke. When using do not eat or drink.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.

Storage class (TRGS 510) : 10, Combustible liquids

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Zinc alkylthiophosphate	68649-42-3	MAK (Inhalable fraction.)	2 mg/m3 Inhalable fraction.	DFG MAK
		MAK (Respirable fraction.)	0,1 mg/m3 Respirable fraction.	DFG MAK



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Safety shoes
Impervious clothing
Wear as appropriate:

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -30 °C

Boiling point/boiling range : No data available

Flash point : 236 °C
Method: Cleveland open cup



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0,874 g/cm ³ (15,6 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: < 7.000 mPa.s (-25 °C)
Viscosity, kinematic	: ca. 108 mm ² /s (40 °C)
Oxidizing properties	: No data available

9.2 Other information

Self-ignition	: No data available
---------------	---------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

ZINC DIALKYL DITHIOPHOSPHATE:

Acute oral toxicity : LD50 (Rat): > 2.000 - 5.000 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Components:

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Acute oral toxicity : LD50 (Rat): > 15 g/kg
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Severe skin irritation

CALCIUM LONG-CHAIN ALKYLPHENATE SULFIDE:

Result: Slight, transient irritation

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Result: Slight, transient irritation

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: No eye irritation

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

ZINC DIALKYL DITHIOPHOSPHATE:

Result: Slight, transient irritation

Result: Risk of serious damage to eyes.

CALCIUM LONG-CHAIN ALKYLPHENATE SULFIDE:

Result: Slight, transient irritation

HYDROTREATED HEAVY PARAFFINIC BASE OIL:



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Result: No eye irritation

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HEAVY PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HEAVY PARAFFINIC DISTILLATE:

No aspiration toxicity classification



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Zinc alkyldithiophosphate
Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

CALCIUM LONG-CHAIN ALKYLPHENATE SULFIDE
Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : May cause long lasting harmful effects to aquatic life.

Distillates (petroleum), hydrotreated heavy paraffinic
Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10.000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

aquatic invertebrates
(Chronic toxicity) Species: **Aquatic invertebrates**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : **Not classified based on available information.**

Long-term (chronic) aquatic hazard : **Not classified based on available information.**

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Zinc alkyldithiophosphate

Partition coefficient: n-octanol/water : Remarks: **No data available**

Distillates (Petroleum), Hydrotreated Heavy Paraffinic

Partition coefficient: n-octanol/water : log Pow: **Expected > 7**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Product	: Send to a licensed waste management company. Do not contaminate ponds, waterways or ditches with chemical or used container. Do not dispose of waste into sewer.
Contaminated packaging	: Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of as unused product. Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : ZINC DIALKYL DITHIOPHOSPHATE

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
DISTILLATES (PETROLEUM),
HYDROTREATED HEAVY
PARAFFINIC (Number on list 28)

(Number on list 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water contaminating class : WGK 3 highly hazardous to water
(Germany)

TA Luft List (Germany) : Total dust:
Not applicable
Inorganic substances in powdered form:
Not applicable
Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
portion Class 1: 88,77 %

Carcinogenic substances:
portion Class 3: 85,29 %

Mutagenic:
Not applicable
Toxic to reproduction:
Not applicable



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: Not On TSCA Inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : 000000273901

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

H411 Toxic to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment



SAFETY DATA SHEET

Valvoline™ ALL CLIMATE 15W40 Motor Oil

Version: 7.0

Revision Date: 02.02.2021

Print Date: 29/11/2021

STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class