Valvoline<sub>II</sub>

SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS DE

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ FE 0W20

Synthetic Motor Oil

Product code : 872583

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

# 1.3 Details of the supplier of the safety data

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

#### 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 0 30-1 92 40

#### **Product Information**

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### **Additional Labelling:**

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

EUH210 Safety data sheet available on request.



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### **Additional advice**

No information available.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC)	Concentration (%)			
	Registration number	No 1272/2008)				
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 40,00 - < 50,00			
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 1,00 - < 2,50			
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 1,00 - < 2,50			
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50			
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50			
Substances with a workplace exposure limit :						
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7		>= 25,00 - < 40,00			

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

SynPower™ FE 0W20 Synthetic Motor Oil

Revision Date: 01.07.2020 Print Date: 27/12/2021 Version: 3.0

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: Nitrogen oxides (NOx)

carbon dioxide and carbon monoxide

#### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

## 6.2 Environmental precautions

**Environmental precautions** : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

# **SECTION 7: Handling and storage**



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

: Keep container tightly closed in a dry and well-ventilated

areas and containers place.

Storage class (TRGS 510) : 10, Combustible liquids

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	AGW (Vapour and aerosols)	5 mg/m3 Vapour and aerosols	DE TRGS 900



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

### 8.2 Exposure controls

#### **Engineering measures**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

# Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:

Impervious clothing

Safety shoes

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : Not applicable

Pour point :  $< -39 \, ^{\circ}\text{C}$ 

Boiling point/boiling range : No data available

Flash point : 208 °C

Method: Pensky-Martens closed cup



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0,843 g/cm3 (15,6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 48 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

Valvoline,

SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

Strong bases

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Inhalation Skin contact

> Eye Contact Ingestion

#### **Acute toxicity**

Not classified based on available information.

#### **Components:**

#### **HEAVY PARAFFINIC DISTILLATE:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### **Components:**

#### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

Valvoline,

SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: No mortality observed at this dose.

**Components:** 

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

**Components:** 

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Components:

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

**Components:** 

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

**HEAVY PARAFFINIC DISTILLATE:** 

Result: Slight, transient irritation



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

II.

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No skin irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No skin irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Method: OECD Test Guideline 431

Result: No skin irritation

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks: Unlikely to cause eye irritation or injury.

Components:

**HEAVY PARAFFINIC DISTILLATE:** 

Result: No eye irritation

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No eye irritation

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Result: No eye irritation

#### Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

#### **Product:**

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

#### Components:

#### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

#### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

#### C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

#### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

# C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

### Carcinogenicity

Not classified based on available information.

#### Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED HEAVY PARAFFINIC BASE OIL:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Components:**

#### C14-16-18 Alkyl phenol:

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

#### **Aspiration toxicity**

Not classified based on available information.

# **Components:**

# **HEAVY PARAFFINIC DISTILLATE:**

May be fatal if swallowed and enters airways.

# Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

# **Further information**

#### **Product:**

Remarks: No data available



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product:** 

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

: Not classified based on available information.

Long-term (chronic) aquatic

hazard

: Not classified based on available information.

#### **Components:**

Distillates (petroleum), hydrotreated heavy paraffinic

: LL50 (Fish): > 100 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10.000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC 10 mg/l Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Species: Aquatic invertebrates

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic : NOELR: >= 1.000 mg/l

toxicity) Exposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEL: 10 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

Test substance: WAF

Method: OECD Test Guideline 211

bis(nonylphenyl)amine

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h
Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test

C14-16-18 Alkyl phenol

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

Exposure time: 72 h
Test Type: static test
Test substance: WAF

Distillates (petroleum), hydrotreated heavy paraffinic

**Ecotoxicology Assessment** 

Short-term (acute) aquatic : Not classified based on available information.

hazard

Long-term (chronic) aquatic : Not classified based on available information.

hazard

# 12.2 Persistence and degradability

# **Components:**

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

bis(nonylphenyl)amine

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

# 12.3 Bioaccumulative potential

# **Components:**

bis(nonylphenyl)amine

Partition coefficient: n- : log Pow: > 7,5

octanol/water

C14-16-18 Alkyl phenol

Partition coefficient: n- : log Pow: > 7,2

octanol/water

# 12.4 Mobility in soil

No data available



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

**Product:** 

Additional ecological

information

: No data available

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

#### **SECTION 14: Transport information**

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

# 14.3 Transport hazard class(es)

Not regulated as a dangerous good

#### 14.4 Packing group

Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

### 14.6 Special precautions for user

Not applicable

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic

pollutants

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (Number on list 28)

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

SynPower™ FE 0W20 Synthetic Motor Oil



Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

Not applicable

Water contaminating class

(Germany)

WGK 3 highly hazardous to water

TA Luft List (Germany)

Total dust: Not applicable

Inorganic substances in powdered form:

Not applicable

Inorganic substances in vapour or gaseous form:

Not applicable

Organic Substances: portion Class 1: 33,6 %

Carcinogenic substances: portion Class 3: 33,6 %

Mutagenic: Not applicable

Toxic to reproduction:

Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS :

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On TSCA Inventory



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### 15.2 Chemical safety assessment

No data available

#### **SECTION 16: Other information**

#### **Further information**

Internal information: 000000260374

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

**H413** May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by

Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

**BEI**: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade



SynPower™ FE 0W20 Synthetic Motor Oil

Version: 3.0 Revision Date: 01.07.2020 Print Date: 27/12/2021

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

**ELINCS**: European List of Notified Chemical Substances

PEC: Predicted Effect Concentration
PEL: Permissible Exposure Limits
PNEC: Predicted No. Effect Concentration

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class