

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

JMC Motorenöl Extra Leichtlauf 10W40 1I

Further trade names

JMC Motorenöl Extra Leichtlauf 10W40 5I (JM-Nr. 558 30 07)

JMC Motorenöl Extra Leichtlauf 10W40 20I (JM-Nr. 558 30 06)

JMC Motorenöl Extra Leichtlauf 10W40 60I (JM-Nr. 558 30 08)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Engine oil

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Johannes J. Matthies GmbH & Co. KG

Street: Hammerbrookstr. 97

Place: D-20097 Hamburg

Telephone: + 49 (0) 40 2 37 21-0

e-mail: info@matthies.de

Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.

Street: 7 Alpha Court, Phoenix Parkway

Place: GB-NN17 5DP Corby

Telephone: + 44 1536 265633

e-mail: info@larsson.uk.com

Internet: www.larsson.uk.com

1.4. Emergency telephone number: + 44 1536 265633

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes serious eye irritation.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Calciumalkarylsulfonat, langkettiges

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 2 of 9

Pictograms:



Hazard statements

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P103	Read label before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	GHS Classification	
68784-31-6	Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	1 - < 2.5 %
	272-238-5	01-2119657973-23
	Eye Dam. 1, Aquatic Chronic 2; H318 H411	
68784-26-9	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	1 - < 2.5 %
	272-234-3	01-2119524004-56
	Aquatic Chronic 4; H413	
36878-20-3	Bis(nonylphenyl)amine	1 - < 2.5 %
	253-249-4	01-2119488911-28
	Aquatic Chronic 4; H413	
722503-68-6	Calciumalkarylsulfonat, langkettiges	1 - < 2.5 %
	682-816-2	
	Skin Sens. 1, Aquatic Chronic 4; H317 H413	
121158-58-5	phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched; phenol, 4-dodecyl-, branched	0,1 - < 0,3 %
	310-154-3	604-092-00-9
	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1 (M-Factor = 10); H360 H314 H318 H400 H410	
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	0,1 - < 0,3 %
	271-529-4	01-2119492627-25
	Skin Sens. 1B; H317	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 3 of 9

General information

Self-protection of the first aider

Immediately remove any contaminated clothing, shoes or stockings. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Provide fresh air. In case of inhalation of aerosols/spray/spray droplets: Consult a physician. Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.
Carbon dioxide (CO₂). Dry extinguishing powder. Foam.

Unsuitable extinguishing media

Strong water jet

5.2. Special hazards arising from the substance or mixture

Non-flammable. Particular hazard due to substance itself, its combustion products or resulting gases: Carbon dioxide (CO₂). Carbon monoxide. Sulphur oxides. Phosphorus oxides. Hydrogen sulphide (H₂S).

5.3. Advice for firefighters

carbon black In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Dispose of waste according to applicable legislation. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation. Special danger of slipping by leaking/spilling product. Wear suitable protective clothing. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 4 of 9

Personal protection equipment: see section 8

Disposal: see section 13

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Apply skin protection cream for preventive skin protection. Wash hands before breaks and after work.

Conditions to avoid: aerosol or mist formation

Advice on protection against fire and explosion

No special fire protection measures are necessary.

When using do not smoke.

Fire class: B (DIN-/EN-Norms: EN2)

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep away from heat. Keep/Store only in original container.

Hints on joint storage

Do not store together with: Food and feedingstuffs, Oxidizing agent

Further information on storage conditions

If product enters soil, it will be mobile and may contaminate groundwater.

7.3. Specific end use(s)

Engine oil

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Apply skin protection cream for preventive skin protection. Keep away from food, drink and animal feedingstuffs. Do not breathe vapour.

Eye/face protection

In fine dispersion/spraying/misting: Wear eye/face protection.

Hand protection

Wear suitable gloves.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

In fine dispersion/spraying/misting: Wear protective gloves and protective clothing.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	yellow-brown	
Odour:	characteristic	
		Test method
pH-Value:	not determined	DIN 51369
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	not determined	
Pour point:	~-27 °C	DIN ISO 3016
Flash point:	> 200 °C	DIN ISO 2592
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Explosive properties		
The product is not explosive.		
Lower explosion limits:	not determined	
Upper explosion limits:	not determined	
Ignition temperature:	not determined	
Auto-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties		
Not oxidising.		
Vapour pressure: (at 20 °C)	< 0,1 hPa	calculated.
Density (at 15 °C):	0,865 g/cm ³	DIN 51757
Water solubility: (at 20 °C)	practically insoluble	
Solubility in other solvents		
Soluble in hydrocarbons. (Mineral oil)		
Partition coefficient:	not determined	
Viscosity / dynamic:	not determined	
Viscosity / kinematic: (at 100 °C)	~14,2 mm ² /s	DIN 51562
Vapour density:	not determined	
Evaporation rate:	not determined	
Solvent separation test:	No data available	
Solvent content:	none	

9.2. Other information

Odour threshold: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 6 of 9

10.2. Chemical stability

No thermal decomposition if stored/handled/transported properly.
(> 65 °C): Gases/vapours, toxic Gases/vapours, combustible (Hydrogen sulphide (H₂S))

10.3. Possibility of hazardous reactions

Reactions possible with oxidising agents.

10.4. Conditions to avoid

Oxidising agent, strong. Etchant and acids.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

none

Further information

No thermal decomposition if stored/handled/transported properly.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.
Irritation of the respiratory tract: Do not breathe gas/vapour.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
121158-58-5	phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched; phenol, 4-dodecyl-, branched			
	oral	LD50 2100 mg/kg	Rat	Manufacturer
	dermal	LD50 15000 mg/kg	Rabbit	Manufacturer
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts			
	oral	LD50 5000 mg/kg	Rat	Manufacturer

Irritation and corrosivity

Causes serious eye irritation.
Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Calciumalkarylsulfonat, langkettiges; Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts)
It can be assumed that the finished product is not skin sensitising, due to the very low content of sensitising substances.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.
Frequently or prolonged contact with skin may cause dermal irritation.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Observations relevant to classification

Has degreasing effect on the skin.

Other observations

No special hazards caused by the product are known if it is used as intended and instructions given on precautionary measures are observed.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 7 of 9

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
68584-23-6	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts				
	Acute fish toxicity	LC50	1,2 mg/l	96 h	Cyprinus carpio (Common Carp)
	Acute algae toxicity	ErC50	>100 mg/l		Desmodesmus subspicatus
	Acute crustacea toxicity	EC50	1000 mg/l	48 h	Daphnia magna (Big water flea)
	Acute bacteria toxicity	(>3200-<=5000 mg/l)		3 h	
					Manufacturer

12.2. Persistence and degradability

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants. Poorly eliminated from water. Not readily biodegradable (according to OECD criteria). Product is partially biodegradable. Significant residues remain.

Waste oils should not be discharged into the sewage system or bodies of water, nor should they be allowed to seep into soil.

12.3. Bioaccumulative potential

The product has not been tested. Do not allow uncontrolled discharge of product into the environment.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
36878-20-3	Bis(nonylphenyl)amine	3,6
121158-58-5	phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched; phenol, 4-dodecyl-, branched	7,1

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The specified waste codes are recommended due to the intended use of the product. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - contaminated packaging

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 8 of 9

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Dispose of this material and its container to hazardous or special waste collection point. Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.
14.4. Packing group: No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
 Water hazard class (D): 2 - obviously hazardous to water
 Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

JMC Motorenöl Extra Leichtlauf 10W40 1I

Print date: 30.06.2020

Product code: 5583004

Page 9 of 9

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)