

**Safety Data Sheet**

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

JMC Getriebeöl Extra GL5 85W-140

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricating agent

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Company name: Johannes J. Matthies GmbH & Co. KG
Street: Hammerbrookstr. 97
Place: D-20097 Hamburg
Telephone: + 49 (0) 40 2 37 21-0
e-mail: info@matthies.de
Internet: www.matthies.de

Supplier

Company name: Larsson UK Ltd.
Street: 7 Alpha Court, Phoenix Parkway
Place: GB-NN17 5DP Corby
Telephone: + 44 1536 265633
e-mail: info@larsson.uk.com
Internet: www.larsson.uk.com

1.4. Emergency telephone number:

+ 44 1536 265633

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208 Contains Alkylamine. May produce an allergic reaction.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
Endocrine disrupting potential none

SECTION 3: Composition/information on ingredients

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 2 of 9

3.2. Mixtures**Chemical characterization**

Mixtures Mineral oil Additive

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
	Alkylamine			0,1 - < 0,25 %
	701-175-2		01-2119456798-18	
	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H317 H400 H410			
1213789-63-9	Alkenylamine, long chain			0,01 < 0,25 %
	627-034-4		01-2119473797-19	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H302 H314 H318 H335 H373 H304 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	701-175-2	Alkylamine	0,1 - < 0,25 %
	inhalation: LC50 = 1,19 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 = 251 mg/kg; oral: LD50 = 612 mg/kg Skin Sens. 1A; H317: >= 5 - 100		
1213789-63-9	627-034-4	Alkenylamine, long chain	0,01 < 0,25 %
	oral: LD50 = 1689 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=10		

Further Information

IP 346: Dimethylsulfoxide (DMSO)-Extraction < 3 %

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Immediately remove any contaminated clothing, shoes or stockings.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Wash with plenty of soap and water.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin and eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

When in doubt or if symptoms are observed, get medical advice.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂), Extinguishing powder, Water spray jet

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 3 of 9

In case of major fire and large quantities: alcohol resistant foam, Water spray jet/Water with tenside additive

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Gases/vapours, harmful,

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Use non-sparking tools.

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Avoid: aerosol or mist formation. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Usual measures for fire prevention.

Further information on handling

Do not put any product-impregnated cleaning rags into your trouser pockets.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 4 of 9

Hints on joint storage

Do not store together with: Strong acid, Strong alkali, Oxidising agent, strong
Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: Heat, UV-radiation/sunlight

7.3. Specific end use(s)

Lubricating agent

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Protective and hygiene measures

Take off immediately all contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Protect skin by using skin protective cream. When using do not eat, drink, smoke, sniff.

Eye/face protection

In fine dispersion/spraying/misting: Wear eye/face protection.

Hand protection

Wear suitable gloves.

Suitable material: NBR (Nitrile rubber)

Breakthrough time:: > 480 min

Thickness of the glove material: >= 0,38 mm

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Usually no personal respirative protection necessary.

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	brown
Odour:	characteristic
Odour threshold:	not determined

pH-Value: not applicable

Changes in the physical state

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 5 of 9

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flash point:	230 °C
Flammability	
Solid/liquid:	@0202.B020243 °C
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
Vapour pressure:	not determined
Density (at 15 °C):	0,9 g/cm ³
Water solubility:	practically insoluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Viscosity / kinematic: (at 40 °C)	427 mm ² /s
Relative vapour density:	not determined

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat, UV-radiation/sunlight Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Strong acid, Strong alkali, Oxidising agent, strong

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide, Gases/vapours, harmful,**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Based on available data, the classification criteria are not met.

Acute toxicity (dermal) ATEmix: (Mixtures estimated) 209,166 mg/kg

Acute toxicity (inhalative) ATEmix: (Mixtures estimated) 425 mg/kg

ATEmix calculated

ATE (oral) 20080,3 mg/kg

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Alkylamine				
	oral	LD50 mg/kg	612	Rat	Manufacturer
	dermal	LD50 mg/kg	251	Rat	Manufacturer
	inhalation (4 h) vapour	LC50	1,19 mg/l	Rat	Manufacturer
	inhalation dust/mist	ATE	0,05 mg/l		
1213789-63-9	Alkenylamine, long chain				
	oral	LD50 mg/kg	1689	Rat	Manufacturer OECD 401

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Alkylamine. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
	Alkylamine					
	Acute fish toxicity	LC50 mg/l	0,078	96 h Piscis	Manufacturer	
	Acute algae toxicity	ErC50 mg/l	0,44	72 h Algae	Manufacturer	
1213789-63-9	Alkenylamine, long chain					
	Acute fish toxicity	LC50 mg/l	0,06	96 h Piscis	Manufacturer	
	Acute algae toxicity	ErC50 mg/l	0,04	72 h Algae	Manufacturer	
	Acute crustacea toxicity	EC50 mg/l	0,011	48 h Daphnia	Manufacturer	
	Crustacea toxicity	NOEC mg/l	0,013	21 d Daphnia	Manufacturer	

12.2. Persistence and degradability

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 7 of 9

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
1213789-63-9	Alkenylamine, long chain			
	OECD 301B	66 %	28	

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Water hazard class: slightly hazardous to water

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

List of Wastes Code - used product

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.1. UN number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 8 of 9

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Segregation group:	8 - hypochlorites

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
M-Factor: Multiplication Factor
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate

Safety Data Sheet

according to UK REACH Regulation

JMC Getriebeöl Extra GL5 85W-140

Revision date: 04.07.2023

Page 9 of 9

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

TI: Technical Instructions

DGR: Dangerous Goods Regulations

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

EG or EC: European Community

IE: Industrial Emissions

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Alkylamine. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)