



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 1
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250



1. IDENTIFICATION ON THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Identification of the product: Oily liquid.
Trade name: OIL KIT FOR AIR FILTER.
Type of product: Mineral oil.
Use: Industrial.
Company identification: BMC Air Filter

Via Rosl , 115. 40059 Medicina (BO) ITALY

Name and function of the responsible person: Michele Vitale - Quality Control Dept - michele.vitale@bmcairfilters.com
Emergency phone nr: 00390516971511
USA emergency phone nr: CHEMTREC: +1-800-262-8200

2. HAZARDS IDENTIFICATION

OSHA regulatory status: Not classified.
Adverse human health effects: There are potential chronic health effects to consider.
NFPA Hazard Ratings (USA): Health: 0 - No unusual hazard.
Flammability: 0 - Not combustible.
Reactivity: 0 - Stable : Not reactive when mixed with water.
Special Notice Key: -- - ---

Carcinogenicity classification

- **Occupational Safety & Health Administration (OSHA):** Not classified.
- **International Agency for Research on Cancer (IARC):** Not classified.
- **National Toxicology Program (NTP) Symptoms relating to use:** Not classified.
- **Inhalation:** Overexposure to vapors may result in headache, nausea.
- **Skin contact:** Prolonged or repeated skin contact with the material may remove natural oils. Prolonged or repeated contact may cause skin to become dry or cracked.
- **Eye contact:** Direct contact with the eyes is likely irritating. Redness. Blurred vision.
- **Ingestion:** Bad taste. Nausea. Abdominal pain. Must not come into contact with food or be consumed.

Note: NFPA ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in this MSDS must be considered.



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 2
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance name	Contents	CAS No	EC No	Annex No	Classification
----------------	----------	--------	-------	----------	----------------

Base oil: distillates solvent-dewaxed heavy paraffinic > 99 %	64742-65-0	265-169-7	649-474-00-6	Contains DMSO < 3% (Note L applicable)	
---	------------	-----------	--------------	--	--

4. FIRST AID MEASURES

First aid measures

- **Inhalation:** Assure fresh air breathing.
- **Skin contact:** Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- **Eye contact:** Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- **Ingestion:** Rinse mouth. Do not induce vomiting. Seek medical advice.

5. FIRE-FIGHTING MEASURES

Hazardous combustion products: Carbon monoxide and carbon dioxide

No naked lights. No smoking.

Prevention:

Extinguishing media

- Suitable extinguishing media:

Oxygen.

Dry chemical.

Water fog.

- Unsuitable extinguishing media:

Do not use a heavy water stream.

- Surrounding fires:

Use water spray or fog for cooling exposed containers.

- Specific hazards:

When exposed to heat, may decompose liberating hazardous gases.

- Special procedures:

Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

Special protective equipment for fire fighters: Do not enter fire area without proper protective equipment, including respiratory protection.



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 3
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Spill area may be slippery.
- Environmental precautions:** Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.
- Clean up methods:** Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Dilute residues and flush. Recover the cleaning water for later disposal. On water, recover/skim from surface and pour out in disposal container.

7. HANDLING AND STORAGE

- General:** Ventilate confined spaces before entering.
- Precautions in handling and storage:** Avoid all unnecessary exposure.
- Storage:** Keep storage temperature below 60°C Store in tightly closed, properly ventilated containers away from heat, sparks, open flame. Keep container closed when not in use.
- Handling:** Handle in accordance with good industrial hygiene and safety procedures. Ensure prompt removal from eyes, skin and clothing. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

8. EXPOSURE CONTROLS /PERSONAL PROTECTION

Personal protection

- **Respiratory protection:** No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation.
- **Hand protection:** In case of repeated or prolonged contact wear gloves.
- **Skin protection:**
No special clothing/skin protection equipment is recommended under normal conditions of use.
- **Eye protection:** Eye protection should only be necessary where liquid could be splashed or sprayed.
- **Ingestion:** When using, do not eat, drink or smoke.
- **Industrial hygiene:** Provide good ventilation in process area to prevent formation of vapor.



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 4
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C:	Liquid.
Color:	Reddish brown.
Odor:	Barely perceptible.
Boiling point [°C]:	> 320
Vapor pressure [20°C]:	< 0.1 Kpa
Relative density, liquid (water=1):	0.874 (15°C)
Viscosity:	45.8 cSt
Solubility in water:	Insoluble.
Flash point [°C]:	> 200

10. STABILITY AND REACTIVITY

Hazardous decomposition products: When heated to decomposition, emits dangerous fumes.

Hazardous reactions: None under normal conditions.

Materials to avoid: Strong oxidizers.

Conditions to avoid: Open flame. Overheating.

11. TOXICOLOGICAL INFORMATION

Rabbit dermal LD50 [mg/kg]: No data available.

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 5
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250

48 Hour-EC50 - *Daphnia magna* [mg/l]: No data available.

CERCLA (US):

RQ (Reportable quantity, section 304 of EPA's List of Lists): Not listed

13. DISPOSAL CONSIDERATION

General:

Avoid release to the environment. Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations.

14. TRANSPORT INFORMATION

General information:

Not classified.

15. REGULATORY INFORMATION

USA:

This document has been prepared in accordance with the MSDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

OSHA hazardous chemical(s):

Not classified.

Carcinogenicity classification: SARA Title III

International Agency for Research on Cancer (IARC): Not classified.

-

- Section 302 - Extremely Hazardous: RQ (Reportable quantity - List of Lists): Not classified.

Substances (EHS)

- Section 311/312 - Hazards under: Not classified.

EPA's hazard categories

- Section 313 - Toxic Chemicals: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. Not classified.

CERCLA information:

RQ (Reportable quantity - List of Lists) : Not classified.

California proposition 65:

Substances listed : Not classified.

Symbol(s):

None.



MATERIAL SAFETY DATA SHEET

According to EC Regulation 830/2015

Page 6
Revised edition no.2
Date 07/01/16
EN

OIL FOR AIR FILTER

WAFLU250

US Toxic
R Phrase(s): None.
S Phrase(s): None.

16. OTHER INFORMATION

Further information: None.

Substances Control Act - TSCA: The components of this product are listed on the TSCA inventory or otherwise comply with TSCA pre-manufacture notification requirements.

This document has been prepared in accordance with the MSDS requirements of the national codes of practice declared by NOHCS under s.38(1) of the National Occupational Health and Safety Commission Act 1985 (Cwth).

DISCLAIMER OF LIABILITY The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 1
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product Name	OIL KIT FOR AIR FILTER
Identification of the product	Oily liquid
Chemical Name	Paraffinic distillate, heavy, solvent-dewaxed
Type of product	Mineral Oil
Synonyms	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified uses	Industrial
---------------------------------	------------

Details of the supplier of the safety data sheet

Company Name	BMC Air Filter
Contact of the responsible person	Michele Vitale – Quality Control Dept – michele.vitale@bmcairfilters.com
Telephone	0039 0516971511
Fax	0039 051852659
Website	www.bmcairfilter.com

Emergency telephone number

Organization	CHEMTREC
Telephone	+1-800-262-8200
Other emergency number	0039 0516971511

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARD RATINGS

Flammability	1
Toxicity	0
Body Contact	0
Reactivity	0
Chronic	0



GHS Classification	Not Applicable
---------------------------	----------------

Label elements

GHS label elements	Not Applicable
---------------------------	----------------



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 2
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

Hazard statements | Not Applicable

Precautionary statements | Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances N.A.

Mixtures

Name	% (weight)	CAS No	EC No	Annex No	Classification
Base oil: distillates solvent-dewaxed heavy paraffinic	<99	64742-65-0	265-169-7	649-474-00-6	-

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye contact	Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin contact	Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Foam.
Dry chemical powder

Special hazards arising from the substrate or mixture

Fire Incompatibility | None known

Advice for firefighters

Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.
Fire/Explosion Hazard	Combustible. Slight fire hazard when exposed to heat or flame.

SECTION 6 ACCIDENTAL RELEASE MEASURES

BMC Air Filter

Via Roslè, 115 40059 Medicina (BO) ITALY



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 3
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

Personal precautions, protective equipment and emergency procedures

Minor Spills	Remove all ignition sources. Clean up all spills immediately.
Major Spills	Clear area of personnel and move upwind.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs..
Other information	Store in original containers. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid contamination of water, foodstuffs, feed or seed.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Source	Ingredient	Material name	TWA	STEL	Notes
US OSHA Permissible Exposure Levels (PELs) – Table Z1	Paraffinic distillate, heavy, solvent-dewaxed	Oil mist, mineral	5 mg/m ³	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Paraffinic distillate, heavy, solvent-dewaxed	Mineral oil, excluding metal working fluids Pure, highly and severely refined / Mineral oil, excluding metal working fluids – Poorly and midly refined	5 mg/m ³	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Paraffinic distillate, heavy, solvent-dewaxed	Heavy mineral oil mist, Paraffinic oil mist, white mineral oil mist	5 mg/m ³	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material Name	TEEL - 1	TEEL - 2	TEEL - 3
Paraffinic distillate, heavy, solvent-dewaxed	Pump oil	15 mg/m ³	170 mg/m ³	990 mg/m ³



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 4
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

Exposure Controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Eye and face protection	Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See hand protection below
Hand protection	Wear general protective gloves, eg. light weight rubber gloves.
	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Relative density (water=1)	0.874 (15°C)
Colour	Reddish brown	Partition coefficient n-octanol / water	N.A.
Odour	Barely perceptible	Auto-ignition temperature (°C)	N.A.
Odour threshold	N.A.	Decomposition Temperature	N.A.
pH	N.A.	Viscosity (cSt)	45.8
Melting point / Freezing point (°C)	N.A.	Flash point	> 200 °C
Boiling point	> 320 °C	Explosive properties	N.A.
Evaporation rate	N.A.	Oxidising properties	N.A.
Flammability	N.A.	Lower Explosive Limit	N.A.
Upper Explosive Limit	N.A.	Vapour pressure (20°C)	< 0.1 Kpa
Volatile component	N.A.	Vapour densit (Air=1)	N.A.
Solubility	Insoluble	VOC g/l	N.A.

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of Hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 5
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has not been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

	TOXICITY	IRRITATION
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration	Effect	Values	Species
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available	Not Available	Not Available	Not Available

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available

Persistence and degradability

Ingredient	Bioaccumulation
Paraffinic distillate, heavy, solvent- dewaxed	Not Available

Mobility in soil

Ingredient	Mobility
Paraffinic distillate, heavy, solvent- dewaxed	Not Available



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 6
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

SECTION 13 DISPOSAL CONSIDERATIONS

Mobility in soil

Product / Packaging disposal
operating in their area.

Each user must
disposal requirements may differ by country, sta

SECTION 14 TRANSPORT INFORMATION

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE)(64742-65-0*) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US - Alaska Limits for Air Contaminants

US - California Permissible Exposure Limits for Chemical Contaminants US

California Proposition 65 - Carcinogens

US - Hawaii Air Contaminant Limits

US - Idaho - Limits for Air Contaminants

US - Michigan Exposure Limits for Air Contaminants

US - Minnesota Permissible Exposure Limits (PELs)

US - Oregon Permissible Exposure Limits (Z-1)

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US Priority List for the Development of Proposition 65 Safe Harbor Levels – No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 16 OTHER INFORMATION

BMC Air Filter

Via Roslè, 115 40059 Medicina (BO) ITALY



MATERIAL SAFETY DATA SHEET

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Page 7
Revised edition no.2
Date 07/01/16
USA.EN

OIL FOR AIR FILTER

WAFLU250

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

NFPA health hazard : 0 – No unusual hazard
NFPA fire hazard: 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



MATERIAL SAFETY DATA SHEET

Page 1
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product Name	OIL KIT FOR AIR FILTER
Identification of the product	Oily liquid
Chemical Name	Paraffinic distillate, heavy, solvent-dewaxed
Type of product	Mineral Oil
Synonyms	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant Identified uses	Industrial
---------------------------------	------------

Details of the supplier of the safety data sheet

Company Name	BMC Air Filter
Contact of the responsible person	Michele Vitale – Quality Control Dept – michele.vitale@bmcairfilters.com
Telephone	0039 0516971511
Fax	0039 051852659
Website	www.bmcairfilter.com

Emergency telephone number

Organization	CHEMTREC
Telephone	+1-800-262-8200
Other emergency number	0039 0516971511

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARD RATINGS

Flammability	1
Toxicity	0
Body Contact	0
Reactivity	0
Chronic	0



CANADIAN WHMIS SYMBOLS



MATERIAL SAFETY DATA SHEET

Page 2
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

GHS Classification | Not Applicable

Label elements

GHS label elements | Not Applicable

Hazard statements | Not Applicable

Precautionary statements | Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances N.A.

Mixtures

Name	% (weight)	CAS No	EC No	Annex No	Classification
Base oil: distillates solvent-dewaxed heavy paraffinic	<99	64742-65-0	265-169-7	649-474-00-6	-

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye contact	Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin contact	Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Foam.
Dry chemical powder

Special hazards arising from the substrate or mixture

Fire Incompatibility | None known

Advice for firefighters

Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.



MATERIAL SAFETY DATA SHEET

Page 3
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

Fire/Explosion Hazard

Combustible.
Slight fire hazard when exposed to heat or flame.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

Remove all ignition sources.
Clean up all spills immediately.

Major Spills

Clear area of personnel and move upwind.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

Avoid all personal contact, including inhalation.
Wear protective clothing when risk of exposure occurs..

Other information

Store in original containers.
Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container

Metal can or drum
Packaging as recommended by manufacturer.
Check all containers are clearly labelled and free from leaks.

Storage incompatibility

Avoid contamination of water, foodstuffs, feed or seed.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Source	Ingredient	Material name	TWA	STEL	Notes
Canada – Yukon Permissible concentration for airborne contaminant	Paraffinic distillate, heavy, solvent- dewaxed	Oil mist, mineral	5 mg/m ³ / --- ppm	10 mg/m ³ / --- ppm	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	Paraffinic distillate, heavy, solvent- dewaxed	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available



MATERIAL SAFETY DATA SHEET

Page 4
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances	Paraffinic distillate, heavy, solvent-dewaxed	Mineral oils, untreated and mildly	Not Available	Not Available	Not Available
Canada – Northwest Territories Occupational Exposure Limits	Paraffinic distillate, heavy, solvent-dewaxed	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available
Canada - Nova Scotia Occupational Exposure Limits	Paraffinic distillate, heavy, solvent-dewaxed	Oil mist, mineral	5 mg/m ³	10 mg/m ³	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Prince Edward Island Occupational Exposure Limits	Paraffinic distillate, heavy, solvent-dewaxed	Mineral oil, excluding metal working fluids - Pure, highly and severely refined / Mineral oil, excluding metal working fluids - Poorly and mildly refined	5 mg/m ³	Not Available	TLV® Basis: URT irr
Canada – Quebec Permissible Exposure Values for Airborne Contaminants	Paraffinic distillate, heavy, solvent-dewaxed	Mineral oil (mist) / Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available
Canada - Alberta Occupational Exposure Limits	Paraffinic distillate, heavy, solvent-dewaxed	Oil mist, mineral	5 mg/m ³	10 mg/m ³	Not Available
Canada – British Columbia Occupational Exposure Limits	Paraffinic distillate, heavy, solvent-dewaxed	Oil mist - mineral, mildly refined / Oil mist - mineral, severely refined	0.2 mg/m ³ / 1 mg/m ³	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material Name	TEEL – 1	TEEL - 2	TEEL - 3
Paraffinic distillate, heavy, solvent- dewaxed	Pump oil	15 mg/m ³	170 mg/m ³	990 mg/m ³

Exposure Controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Eye and face protection	Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See hand protection below



MATERIAL SAFETY DATA SHEET

Page 5
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

Hand protection	Wear general protective gloves, eg. light weight rubber gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Relative density (water=1)	0.874 (15°C)
Colour	Reddish brown	Partition coefficient n-octanol / water	N.A.
Odour	Barely perceptible	Auto-ignition temperature (°C)	N.A.
Odour threshold	N.A.	Decomposition Temperature	N.A.
pH	N.A.	Viscosity (cSt)	45.8
Melting point / Freezing point (°C)	N.A.	Flash point	> 200 °C
Boiling point	> 320 °C	Explosive properties	N.A.
Evaporation rate	N.A.	Oxidising properties	N.A.
Flammability	N.A.	Lower Explosive Limit	N.A.
Upper Explosive Limit	N.A.	Vapour pressure (20°C)	< 0.1 Kpa
Volatile component	N.A.	Vapour densit (Air=1)	N.A.
Solubility	Insoluble	VOC g/l	N.A.

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of Hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has not been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.



MATERIAL SAFETY DATA SHEET

Page 6
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

Skin Contact	The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

	TOXICITY	IRRITATION
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration	Effect	Values	Species
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available	Not Available	Not Available	Not Available

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Paraffinic distillate, heavy, solvent- dewaxed	Not Available	Not Available

Persistence and degradability

Ingredient	Bioaccumulation
Paraffinic distillate, heavy, solvent- dewaxed	Not Available

Mobility in soil

Ingredient	Mobility
Paraffinic distillate, heavy, solvent- dewaxed	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Mobility in soil

Product / Packaging | Legislation addressing waste disposal requirements may differ by country, state and/ or territory. **disposal** Each user must refer to laws operating in their area.

SECTION 14 TRANSPORT INFORMATION



MATERIAL SAFETY DATA SHEET

Page 7
Revised edition no.2
Date 07/01/16
CAN.EN

OIL FOR AIR FILTER

WAFLU250

Land transport (Not Applicable): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, HEAVY, SOLVENT-DEWAXED (SEVERE)(64742-65-0*) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits (English)

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens Canada

Quebec Permissible Exposure Values for Airborne Contaminants (French)

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits

Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Forensic Identification Services Chemical Carcinogenicity Evaluation - Table 1 - Chemicals Considered for Assessment (English)

Forensic Identification Services Chemical Carcinogenicity Evaluation - Table 1 - Chemicals Considered for Assessment (French) International

Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

SECTION 16 OTHER INFORMATION

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

NFPA health hazard : 0 – No unusual hazard
NFPA fire hazard: 1 - Must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product